



**OMNITRONIC CFL Live mixer**

Live mixer

- 12/16/24/32 mono inputs with XLR sockets
- +48 V phantom power per channel
- 2 stereo effect returns
- 4 groups for levelling complete signal groups
- Separate master, group, monitor outputs

- No. 10060300.....CFL-1242
- No. 10060325.....CFL-1642
- No. 10060350.....CFL-2442
- No. 10060375.....CFL-3242



**Technical specifications:**

Device:	CFL-1242	CFL-1642	CFL-2442	CFL-3242
Power supply:	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~
Power consumption:	40 W	50 W	70 W	100 W
Inputs:				
mono	12 XLR or balanced 6.3 mm jacks	16 XLR or balanced 6.3 mm jacks	24 XLR/6.3 mm jack, balanced	32 XLR or balanced 6.3 mm jacks
inserts	12 6.3 mm jacks, unbalanced	16 6.3 mm jacks, unbalanced	24 6.3 mm jack, unbalanced	32 6.3 mm jacks, unbalanced
stereo	2 6.3 mm jacks	2 6.3 mm jacks	2 6.3 mm jacks	2 6.3 mm jacks
4 Aux-Return	balanced 6.3 mm jacks	balanced 6.3 mm jacks	balanced 6.3 mm jacks	balanced 6.3 mm jacks
Outputs:				
2 Main Mix Out	XLR or balanced 6.3 mm jacks	XLR or balanced 6.3 mm jacks	XLR/6.3 mm jack, balanced	XLR or balanced 6.3 mm jacks
1 Monitor	balanced 6.3 mm jack	balanced 6.3 mm jack	balanced 6.3 mm jack, balanced	balanced 6.3 mm jack
4 Group-Out:			6.3 mm jack, balanced	6.3 mm jack
4 Aux-Send	balanced 6.3 mm jack	balanced 6.3 mm jack	6.3 mm jack, balanced	balanced 6.3 mm jack
Rec Out	RCA	RCA	RCA	RCA
Frequency range:	10 Hz - 60 kHz, ±3 dB	10 Hz - 60 kHz, ±3 dB	10 Hz - 60 kHz, ±3 dB	10 Hz - 60 kHz, ±3 dB
Dimensions (WxDxH):	530 x 530 x 160 mm	780 x 530 x 160 mm	1005 x 530 x 160 mm	1290 x 530 x 160 mm
Weight:	14 kg	16 kg	18 kg	19 kg