



-110-230V
50-60Hz

VOLTAGE SELECT SWITCH



CIRCUIT GND TO CHASSIS SWITCH



GROUND UNGROUND



DC OUTPUT TERMINAL

- PIN1: +1.7V
- PIN2: -1.7V
- PIN3: GROUND
- PIN4: +48V
- PIN5: SHIELD
- PIN6: SWITCH OUTPUT RELAYS

CAUTION

Never open the enclosure cover. Keep away from electrical equipment from mains before changing fuse. Replace the fuse only with the same type and rating. Never open the housing! There are no serviceable parts inside the device. Maintenance and service operations only by authorized dealer.

Nei casi di manutenzione non aprire mai l'enclosure. Evitare di toccare l'elettronica prima di cambiare il fusibile. Sostituire il fusibile solo con lo stesso tipo e rating. Non aprire mai il case! Non ci sono parti riparabili all'interno dell'apparecchio. La manutenzione e i servizi sono riservati ai rivenditori autorizzati.

Bei Wartungsarbeiten niemals Gehäuse öffnen. Vor dem Wechseln des Sicherungsglases niemals die Gehäuse öffnen! Es gibt keine reparierbaren Teile. Wartungs- und Servicearbeiten nur durch autorisierten Fachhändler.

Do not make changes to the enclosure. Do not open the front cover. Do not touch the components inside. Only an authorized dealer may change the mains fuse. Do not attempt to repair. Contact the representative contact person in your area for maintenance and service operations only by authorized dealer.

Type: PDSO Micro-series
Power Supply Unit
Power supply: 230 V AC, 50 Hz
Power consumption: 250 W
Fuse: T 5 A, 250 V



www.abb.com