



OMNITRONIC MZD-88 Matrix zone distributor

8-channel audio mixer with matrix

- 8 inputs with matrix assignment to 8 mono/4 stereo zones
- Level and PAN control per zone
- Ultra flexible signal distribution



No. 10304120

Technical specifications:

Power supply:	115/230 V, 50/60 Hz ~
Power consumption:	10 W
Frequency range:	20-20000 Hz
Dynamic range:	100 dB
Max. input level:	+21 dBu
Input impedance:	10 kohm
Max. gain:	+12 dB, per channel
Dimensions (WxDxH):	482 x 195 x 89 mm
Weight:	3.5 kg



OMNITRONIC MLM-81 Microphone line mixer

Microphone line mixer, 8 channels

- For mixing up to 8 mono input signals to 1 mono output
- Each mic input with optional 12 V phantom power via dip switches
- 6.3 mm inputs convertible into line outputs



No. 10304150

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	10 W
Input impedance:	600 ohms (Mic), 18 kohms (Line), 10 kohms (Aux Bus)
Max. input level:	-23 dBV (Mic), +22 dBV (Line)
Phantom power:	12 V
Max. output level:	+17 dBV
Output impedance:	51 ohms
Max. gain:	69 dB (Mic), 26 dB (Line)
Distortion:	<0.003 %
S/N ratio:	106 dB
Dimensions (WxDxH):	482 x 152 x 44 mm
Weight:	3 kg



OMNITRONIC TS-8 Isolator/splitter

8-channel line isolator/splitter

- Converts 1/4" and RCA signals into balanced XLR signals or vice versa
- Separate input and output signal grounds reduce hum
- Very clean and neutral sound



No. 10304151

Technical specifications:

Frequency range:	10 Hz - 50 kHz, ± 5 dB @ +4 dBu
THD:	0.01% typical @ 0.1 kHz, +18 dBu, <1% @ 100 Hz, +24 dBu
Channel separation:	90 dB typical
CMRR: 60 dB typical	
Phase error:	<5°, 20-20000 Hz
Insertion loss:	0.4 dB @ 100 kohm 5.5 dB @ 600 ohm
Audio connectors:	XLR, balanced; 6.3 mm jack (1/4"), balanced; RCA stereo
Dimensions:	483 x 115 x 45 mm
Weight:	2 kg



OMNITRONIC MPP-24 Mini patch panel

Combined patch panel and power supply

- 2 XLR line inputs and 2 XLR feed-through outputs
- Speaker connectors for Low, Mid/High and bi-amping operation
- Powercon input and output



Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Max. power output:	3680 W
Max. total current:	16 A
Dimensions (WxHxD):	482 x 46 x 85 mm (19", 1 U)
Weight:	1.5 kg

No. 10453050 silver
No. 10453051 black