

OMNITRONIC DB-100 Decibel level meter

Level display for audio signals

- 1 stereo channel
- Sensitivity adjustable
- 40-digit LED displays, separated into 3 color segments



Technical specifications:

| | |
|---------------------|--|
| Power supply: | 230 V AC, 50 Hz ~, via supplied power unit |
| Power consumption: | 5 W |
| Input sensitivity: | approx. 350 mV - 7 V |
| Display range: | -57 dB - 0 dB (in 3 dB steps) |
| Audio inputs: | stereo RCA |
| Dimensions (WxHxD): | 482 x 52 x 44 mm (19", 1 U) |
| Weight: | 780 g |

No. 10453010 silver
No. 10453012 black

OMNITRONIC DB-200B Decibel level meter

2-channel level display for audio signals

- 2 stereo channels
- Sensitivity adjustable
- 40-digit LED displays, separated into 3 color segments



Technical specifications:


| | |
|---------------------|--|
| Power supply: | 230 V AC, 50 Hz ~, via supplied power unit |
| Power consumption: | 5 W |
| Input sensitivity: | approx. 350 mV to 7 V |
| Display range: | -27 dB - 0 dB (in 3 dB steps) |
| Audio inputs: | stereo RCA |
| Dimensions (WxHxD): | 482 x 55 x 44 mm (19", 1 U) |
| Weight: | 730 g |

No. 10453014 silver
No. 10453016 black

OMNITRONIC AN-31XL Audio analyzer

31-band analyzer for audio signals

- Realtime analysis of audio signals
- Analysis meter with 12 LEDs per frequency band
- Pink noise generator, adjustable
- Incl. measurement microphone



No. 10355790

Technical specifications:

| | |
|----------------------------|--|
| Power supply: | 230 V AC, 50 Hz ~ |
| Power consumption: | 10 W |
| Number of frequency bands: | 31 |
| Frequency range: | 20 - 20000 Hz |
| Frequency indication: | 20/25/31.5/40/50/63/80/100/125/160/200/250/315/400/500/630/800 Hz/ 1/1.25/1.6/2/2.5/3.15/4/5/6.3/8/10/12.5/16/20 kHz |
| LEDs per frequency band: | 12 |
| Level indication: | -38 dB to +10 dB |
| Audio inputs: | 2 x 6.3 mm mono jack (mic), 1 x stereo RCA (line), switchable |
| Pink noise output: | stereo RCA |
| Dimensions: | 483 x 170 x 88 mm (19", 2 U) |
| Weight: | 3 kg |