

No. 30226750



NEUTRIK NYS-SPP-L1 Patchpanel

Neutrik NYS-SPP-L1 patchbay

- Balanced multi-functional 48-point patchbay with 3 operating modes (NORMAL, THRU, HALF NORMAL)



OMNITRONIC LUB-27 Speaker switch box

Speaker/amplifier switch box with IR remote control

- 7-channel switch box for passive speaker pairs or amplifiers
- Ideal solution for performance comparison in showrooms
- Incl. IR remote control



Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
	via supplied power unit 12 V/1.5 A
Power consumption:	30 W
Rated power:	25 A per channel
Connectors:	pairs of screw terminals
Remote control:	2 x 1.5 V micro batteries (type AAA)
Coverage:	10 m
Extension connection:	3.5 mm jack
Dimensions (LxWxH):	482 x 220 x 78 mm (19", 2 U)
Weight:	3.2 kg

No. 10453007

No. 10453008.....Y-cable

No. 10453009.....IR extension



USB RJ45

OMNITRONIC DXM-1616 Matrix

Digital matrix-controller with software

- 16 inputs and 16 outputs with flexible signal routing
- 48 kHz sampling rate
- 24 bit A-D/D-A-converter



No. 10356380

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
Inputs:	16, active, balanced
Gain range:	-40 dB to +6 dB
Input impedance:	10 kohms
Frequency Response:	20-20000 Hz
Outputs:	16, active, balanced
Output impedance:	<50 mohms (electronically balanced)
Output gain range:	-40 dB to +6 dB
Maximum output level:	+20 dBu
THD:	0.01 %
Delay:	0-1365 ms
Filters:	
HPF:	10 Hz - 16 kHz
LPF:	35 Hz - 20.2 kHz
Slopes:	6, 12, 18, 24 or 48 dB/octave
Type:	Bessel, Butterworth or Linkwitz-Riley
Equalizers:	
PEQ:	20-20000 Hz
LOSHF:	20 Hz - 1 kHz
HISHF:	1 kHz - 20 kHz
Q-value:	0.4-128
Gain:	±12 dB; 0.1 dB
Compressor:	
Threshold:	-24 to +12 dB; 1 dB
Ratio:	1:128 to 128:128
Boost:	x1, x2, x 4, x8
Limiter:	
Threshold:	-53 to +10 dB; 0.5 dB
Attack:	20 μs to 3 ms/dB
Release:	10 ms/dB to 5 sec/dB
Noise Gate:	
Threshold:	-66 to -24 dB; 1 dB
Attack:	0.1 ms to 100 ms/dB
Release:	10 ms/dB to 5 sec/dB
Dimensions (WxHxD):	482 x 88 x 230 mm
Weight:	7.2 kg