

NEW

OMNITRONIC DJP-700 Class-D Amplifier

Compact stereo mixing amplifier 2 x 300 W

- Silent operation due to fanless cooling concept
- Extremely low weight and height due to integrated switch mode power supply
- 2 operating modes can be selected (stereo or bridged)
- Speaker switch-on delay and auto limiters
- Extensive protective circuits
- Robust steel chassis with aluminum front panel
- 4 stereo line inputs, 1 mic input, 1 Aux input



No. 10451601

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	130 W (1/8 power)
Power output sine:	
stereo 4 ohms	2 x 300 W
stereo 8 ohms	2 x 200 W
8 ohms bridged	1 x 600 W
Frequency range:	20-20000 Hz, ± 0.5 dB
Damping factor:	>300
Distortion factor:	0.05 %
Slew rate:	14 V/μsec
S/N ratio:	100 dB
Input impedance:	20 kohms (balanced), 10 kohms (unbalanced)
Input sensitivity:	1 V
Input connectors:	
Line 1-4:	RCA L/R
Mic:	combination XLR/6.3 mm jack, unbal.
Aux:	3.5 stereo jack
Output connectors:	
Master:	RCA L/R
Speaker:	screw connectors
Circuitry:	class D
Control elements:	power switch, source selector, level/tone controls, mode switch (stereo/bridged)
LED indicators:	power
Protection circuits:	softstart, short-circuit, overheat, clipping, overload, VHF signals, DC voltage
Construction:	steel chassis, aluminum front
Dimensions (DxWxH):	256 x 233 x 44 mm
Weight:	2.2 kg

NEW

USB SDHC BLUETOOTH MP3

OMNITRONIC DJP-700P Class-D Amplifier

Compact stereo mixing amplifier with audio player and Bluetooth 2 x 300 watts

- Built-in audio player with Bluetooth receiver for wireless music streaming
- USB 2.0 input and SD card slot
- Silent operation due to fanless cooling concept
- Extremely low weight and height due to integrated switch mode power supply
- 2 operating modes can be selected (stereo or bridged)
- Speaker switch-on delay and auto limiters
- 4 stereo line inputs, 1 mic input, 1 Aux input
- Extensive protective circuits
- Robust steel chassis with aluminum front panel



No. 10451602

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	130 W (1/8 power)
Power output sine:	
stereo 4 ohms	2 x 300 W
stereo 8 ohms	2 x 200 W
8 ohms bridged	1 x 600 W
Frequency range:	20-20000 Hz, ± 0.5 dB
Damping factor:	>300
Distortion factor:	0.05 %
Slew rate:	14 V/μsec
S/N ratio:	100 dB
Input impedance:	20 kohms (balanced), 10 kohms (unbalanced)
Input sensitivity:	1 V
Input connectors:	
Line 1-4:	RCA L/R
Mic:	combination XLR/6.3 mm jack, unbal.
Aux:	3.5 stereo jack
Output connectors:	
Master:	RCA L/R
Speaker:	screw connectors
Circuitry:	class D
Control elements:	power switch, source selector, level/tone controls, mode switch (stereo/bridged)
LED indicators:	power
Protection circuits:	softstart, short-circuit, overheat, clipping, overload, VHF signals, DC voltage
Construction:	steel chassis, aluminum front
Dimensions (DxWxH):	256 x 233 x 44 mm
Weight:	2.2 kg
Audio player:	
Playback format:	MP3, WMA, WAV
Available storage media:	USB devices and SD(HC) cards up to 32 GB
File system:	FAT16/32
Bluetooth:	
Carrier frequency:	2.4 GHz
Range:	approx. 10 m