



DDA Series

High impulse stability, low weight, small size (2 rack units) and the integrated switch mode power supply: That are the benefits of the class D amplifiers **PSSO DDA** and **PSSO QDA**. The amps also feature limiters, speaker on delay and 3 adjustable operating modes (stereo, parallel, bridge).

LED-VU meters are integrated into the solid steel housing as well as LEDs for protect, clip and signal. High efficient air flow from the front to the back and temperature controlled fans prevent thermal problems.

NEW CLASS D 19" 2U

No. 10451684



PSSO DDA-1700 Amplifier

Stereo PA amplifier with SMPS, 2 x 850 W / 4 ohms

NEW CLASS D 19" 2U

No. 10451685



PSSO DDA-2500 Amplifier

Stereo PA amplifier with SMPS, 2 x 1250 W / 4 ohms

NEW CLASS D 19" 2U

No. 10451687



PSSO DDA-3500 Amplifier

Stereo PA amplifier with SMPS, 2 x 1750 W / 4 ohms

NEW CLASS D 19" 2U

No. 10451695



PSSO QDA-4400 4-Channel Amplifier

PA amplifier with SMPS, 4 x 1100 W / 4 ohms, 4 x 650 W / 8 ohms



CLASS I 2U

No. 10451696



PSSO QCA-6400 4-Channel SMPS Amplifier

PA amplifier with SMPS, 4 x 1600 W / 2 ohms, 4 x 1400 W / 4 ohms

CLASS I 2U

No. 10451697



PSSO QCA-10000 4-Channel SMPS Amplifier

PA amplifier with SMPS, 4 x 2150 W / 2 ohms, 4 x 2100 W / 4 ohms