



OMNITRONIC DD-5220L Turntable

Direct drive DJ turntable "Ultra Torque" with switchable phono/line output

- Direct drive
- Initial torque >4.5 kg/cm
- Adjustable start/stop time
- Tone arm height adjustable
- Phono/line output
- Delivery includes slipmat



black



Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	15 W
Type:	3-speed full manual turntable
Drive method:	Quartz-controlled direct drive
Motor:	Brushless DC motor
Turntable platter:	d=332 mm, 1400 g
Speed:	33 1/3 RPM, 45 RPM and 78 RPM
Speed change time:	< 1 sec
Rotation-direction:	Forwards/backwards
Pitch adjustment:	±10 %, ±20 %, ±50 %
Initial torque:	> 2.1 kg/cm
Wow and flutter:	< 0.20 % WRMS
Start time:	< 1 sec
Stop time:	< 1 sec (¼ rotation)
Rumble:	50 dB DIN B
Tonearm:	S-shape with Cardan's suspension
Tonearm length:	234 mm
Adjustable tonearm height:	8-10.5 mm
Overhang:	20 mm
Adjustable stylus pressure	0-4 g
Connectors:	1 x stereo RCA
Dimensions:	450 x 352 x 148 mm
Weight:	11 kg

No. 10603003.....DD-5220L, black
No. 10603006.....Dust-cover

USB PCconnect

OMNITRONIC DD-2520/2550 USB Turntable bk

Direct-drive DJ turntable with switchable phono/line output

- USB interface
- Incl. recording software
- Precision direct drive
- Switchable phono/line output
- Tone arm height adjustable
- Delivery includes pick-up system
- Delivery includes slipmat



silver



black



Technical specifications:

Power supply:	115/230 V, 50/60 Hz ~
Power consumption:	12 W
Type:	Manual turntable
Drive method:	Direct drive
Motor:	Brushless 24 V DC motor
Speed:	33 1/3 RPM and 45 RPM
Change time between speeds:	33 -> 45 RPM in <1 sec 45 -> 33 RPM in <1 sec
Pitch adjustment:	± 10 % via fader
Initial torque:	>1.0 kg/cm
Start time:	<1 sec
Stop time:	<1 sec
Wow and flutter:	<0.15 %
Rumble:	55 dB DIN B
Platter:	Outer diameter 330 mm, Weight 728 g
Tonearm:	S-shape with Cardan's suspension
Tonearm length:	230.5 mm
Overhang:	16 mm
Adjustable stylus pressure	0-4 g
Anti-skating range:	0-7 g
Phono output level:	1.5-3.6 mV/ 1 kHz 5 cm/sec
Line output level:	90-216 mV/ 1 kHz 5 cm/sec
Channel separation:	>15 dB
Output connectors:	RCA, USB type B
Dimensions:	450 x 350 x 155 mm
Weight:	11 kg

No. 10603060.....DD-2520, black
No. 10603061.....DD-2550, silver