

Neutral Sound

ARM-6.5 2-Way Studio Monitor

The high-resolution active speaker system is ideally suitable as monitor system in studios and for all other applications requiring crystal clear and precise sound reproduction. The ribbon technology enables playback in its most natural form. This monitor sounds as natural and detailed as a studio monitor should. It has a 16.5 cm bass-midrange speaker with Kevlar cone for rich and defined bass response and separate power amplifiers (class A/B) for efficient control of the woofer and ribbon transducer. 3 EQ selectors are provided to adapt to various acoustic conditions. The click type rotary volume control at the front allows for precise level adjustment.

Black high-gloss surface

Crystal clear and precise listening experience through built-in 3 cm velocity ribbon tweeter (2") with wave guide

16.5 cm bass-midrange speaker (6.5") with Kevlar cone

Max. SPL: 102 dB
Frequency range: 45 Hz - 22 kHz
Crossover frequency: 2,8 kHz

Separate power amplifiers for bass speaker and tweeter (bi-amping) with efficient class AB circuitry

Dimensions (LxWxH): 275 x 230 x 358 mm
Weight: 7 kg



Click type rotary volume control at front for precise level adjustment



ACTIVE BI AMP

No. 11036458

OMNITRONIC ARM-6.5 2-Way Studio Monitor

Active 2-way reference studio monitor with ribbon transducer and Kevlar woofer