



ACTIVE

## OMNITRONIC C active 2x

Active speaker pair

- Active 2-way system
- 13 - 20 cm woofer (5 - 8") and 2.5 cm dome tweeter (1")
- Clear and powerful sound
- Rugged ABS plastic housing
- Movable mounting bracket
- 2-band EQ

|                   |                    |
|-------------------|--------------------|
| No. 11036716..... | C-50A, 13 cm black |
| No. 11036717..... | C-50A, 13 cm white |
| No. 11036720..... | C-60A, 16 cm black |
| No. 11036721..... | C-60A, 16 cm white |
| No. 11036724..... | C-80A, 20 cm black |
| No. 11036725..... | C-80A, 20 cm white |

### Technical specifications:

| Device:                 | C-50 active                            | C-60 active                                | C-80 active                            |
|-------------------------|--|--|--|
| Color:                  | black/white                            | black/white                                | black/white                            |
| Power supply:           | 230 V AC, 50 Hz ~                      | 230 V AC, 50 Hz ~                          | 230 V AC, 50 Hz ~                      |
| Rated power:            | 50 W RMS                               | 60 W RMS                                   | 80 W RMS                               |
| Program power:          | 80 W                                   | 100 W                                      | 125 W                                  |
| Components:             | 13 cm woofer (5"), 2.5 cm tweeter (1") | 16.5 cm woofer (6.5"), 2.5 cm tweeter (1") | 20 cm woofer (8"), 2.5 cm tweeter (1") |
| Input:                  | 3-pin XLR                              | 3-pin XLR                                  | 3-pin XLR                              |
| Output:                 | 3-pin XLR                              | 3-pin XLR                                  | 3-pin XLR                              |
| Sensitivity:            | 89 dB (1 W, 1 m)                       | 89 dB (1 W, 1 m)                           | 90 dB (1 W, 1 m)                       |
| Frequency range:        | 50 Hz - 20 kHz                         | 50 Hz - 20 kHz                             | 50 Hz - 20 kHz                         |
| Dimensions (H x W x D): | 230 x 180 x 166 mm                     | 285 x 205 x 180 mm                         | 360 x 270 x 240 mm                     |
| Weight:                 | 3 kg (piece)                           | 4.5 kg (piece)                             | 8 kg (piece)                           |



NEW

## OMNITRONIC QI Coaxial wall speaker

Universal wall speaker

- 16-ohm PA wall speaker with an excellent sound for general applications
- 2-way coaxial system with 13/20 cm woofer (5/8")
- Quality MDF cabinet 16 mm
- Movable mounting bracket for ceiling or wall installation
- Screw plug terminal for serial connection

|                   |             |
|-------------------|-------------|
| No. 11038940..... | QI-5, black |
| No. 11038941..... | QI-5, white |
| No. 11038945..... | QI-8, black |
| No. 11038946..... | QI-8, white |

### Technical specifications:

| Device:                 | QI-5                                  | QI-8                                  |
|-------------------------|---------------------------------------|---------------------------------------|
| Rated power:            | 30 W RMS                              | 40 W RMS                              |
| Program power:          | 60 W                                  | 80 W                                  |
| Components:             | 13 cm woofer (5"), 18 mm dome tweeter | 20 cm woofer (8"), 25 mm dome tweeter |
| Connection:             | Screw plug terminal                   | Screw plug terminal                   |
| Impedance:              | 16 ohms                               | 16 ohms                               |
| Sensitivity:            | 90 dB (1 W, 1 m)                      | 91 dB (1 W, 1 m)                      |
| Frequency range:        | 65 Hz - 20 kHz                        | 65 Hz - 20 kHz                        |
| Dimensions (L x W x H): | 188 x 182 x 181 mm                    | 222 x 252 x 252 mm                    |
| Weight:                 | 4 kg (incl. bracket)                  | 5.5 kg (incl. bracket)                |