

IP44

OMNITRONIC OD-2 Wall speaker 2x

Universal wall speaker pair

- Passive (8 ohms) speaker system for general applications
- 1-way system with 30 W power
- 6 cm full-range speaker (2.5")
- Attractive ABS plastic cabinet (scratch-resistant) with metal grille
- Durable mounting plate with joint for panning and tilting allows ceiling or wall installation in most varying angles



Technical specifications:

Rated power:	15 W RMS
Program power:	30 W
Speaker:	6 cm (2.5")
Connection:	spring clamps
Sensitivity:	88 dB (1 W, 1 m)
Max. SPL:	92 dB (1 m)
Impedance:	8 ohms
Frequency range:	150 Hz - 22 kHz
Dispersion angle (HxV):	60° x 60°
Dimensions (L x W x H):	111 x 87 x 90 mm
Weight (piece):	0.5 kg (incl. mounting plate)

No. 11036900 OD-2, black
 No. 11036901 OD-2, white

IP44

OMNITRONIC OD-22 Wall speaker

Universal wall speaker system

- Passive (8 ohms) speaker system for general applications
- 2 x 6 cm full-range speaker with 2 x 2.5"
- 3.5 x 6 cm passive membrane
- Durable mounting plate with joint for panning and tilting allows ceiling or wall installation in most varying angles



Technical specifications:

Rated power:	15 W RMS
Program power:	30 W
Speaker:	2 x 6 cm (2 x 2.5")
Connections:	spring clamps
Sensitivity:	88 dB (1 W, 1 m)
Max. SPL:	95 dB (1 m)
Impedance:	8 ohms
Frequency range:	120 Hz - 22 kHz
Dispersion angle (HxV):	60° x 60°
Dimensions (H x W x D):	110 x 209 x 109 mm
Weight:	0.9 kg (incl. mounting plate)

No. 11036906 OD-22, black, 8ohms
 No. 11036907 OD-22, white, 8ohms