



## OMNITRONIC DX 3-way speaker

Rugged full-range speaker-system

- 3-way party speaker-system for disco and rock music
- 20 cm woofer (8"), piezo, horn
- High-quality horn for smooth mid-range
- Piezo super-tweeters for powerful treble
- Very high durability

|                    |         |
|--------------------|---------|
| No. 11037055 ..... | DX-822  |
| No. 11037061 ..... | DX-1022 |
| No. 11037071 ..... | DX-1222 |
| No. 11037081 ..... | DX-1522 |
| No. 11037085 ..... | DX-2022 |
| No. 11037087 ..... | DX-2222 |
| No. 11037091 ..... | DX-2522 |

### Technical specifications:

| Device:                 | DX-822                         | DX-1022                         | DX-1222                         | DX-1522                         | DX-2022                                 | DX-2222                                 | DX-2522                                    |
|-------------------------|--------------------------------|---------------------------------|---------------------------------|---------------------------------|---|---|--|
| Rated power:            | 150 W RMS                      | 200 W RMS                       | 300 W RMS                       | 400 W RMS                       | 400 W RMS                               | 500 W RMS                               | 600 W RMS                                  |
| Program power:          | 300 W                          | 400 W                           | 600 W                           | 800 W                           | 800 W                                   | 1000 W                                  | 1200 W                                     |
| Components:             | 20 cm woofer (8"), piezo, horn | 25 cm woofer (10"), piezo, horn | 30 cm woofer (12"), piezo, horn | 38 cm woofer (15"), piezo, horn | 2 x 25 cm woofer (2 x 10"), piezo, horn | 2 x 30 cm woofer (2 x 12"), piezo, horn | 2 x 38 cm woofer (2 x 15"), 2 piezos, horn |
| Connections:            | 2 Speaker sockets              | 2 Speaker sockets               | 2 Speaker sockets               | 2 Speaker sockets               | 2 Speaker                               | 2 Speaker sockets                       | 2 Speaker sockets                          |
| Sensitivity:            | 93 dB (1 W, 1 m)               | 95 dB (1 W, 1 m)                | 96 dB (1 W, 1 m)                | 97 dB (1 W, 1 m)                | 96 dB (1 W, 1 m)                        | 99 dB (1 W, 1 m)                        | 101 dB (1 W, 1 m)                          |
| Impedance:              | 8 ohms                         | 8 ohms                          | 8 ohms                          | 8 ohms                          | 8 ohms                                  | 8 ohms                                  | 8 ohms                                     |
| Frequency range:        | 50 - 18000 Hz                  | 50 - 18000 Hz                   | 30 - 18000 Hz                   | 30 - 18000 Hz                   | 45-20000 Hz                             | 30 - 18000 Hz                           | 30 - 18000 Hz                              |
| Dimensions (H x W x D): | 400 x 320 x 280 mm             | 465 x 360 x 310 mm              | 520 x 360 x 310 mm              | 655 x 475 x 355 mm              | 780 x 350 x 330 mm                      | 910 x 375 x 360 mm                      | 1060 x 500 x 405 mm                        |
| Weight:                 | 9 kg                           | 9.5 kg                          | 13 kg                           | 16 kg                           | 15 kg                                   | 18 kg                                   | 40 kg                                      |

## OMNITRONIC BX Subwoofer

Powerful subwoofer

- 300-600 W RMS
- Passive crossover
- Good extension for DX, DS, TX or TMX



|                    |         |
|--------------------|---------|
| No. 11037705 ..... | BX-1250 |
| No. 11037711 ..... | BX-1550 |
| No. 11037731 ..... | BX-1850 |
| No. 11037745 ..... | BX-2250 |
| No. 11037751 ..... | BX-2550 |

### Technical specifications:

| Device:                 | BX-1250            | BX-1550            | BX-1850            | BX-2250                    | BX-2550                    |
|-------------------------|--------------------|--------------------|--------------------|----------------------------|----------------------------|
| Rated power:            | 300 W RMS          | 400 W RMS          | 600 W RMS          | 400 W RMS                  | 600 W RMS                  |
| Program power:          | 600 W              | 800 W              | 1200 W             | 800 W                      | 1200 W                     |
| Components:             | 30 cm woofer (12") | 38 cm woofer (15") | 45 cm woofer (18") | 2 x 30 cm woofer (2 x 12") | 2 x 38 cm woofer (2 x 15") |
| Connections:            | 2 Speaker sockets  | 2 Speaker sockets  | 2 Speaker sockets  | 2 Speaker sockets          | 2 Speaker sockets          |
| Sensitivity:            | 96 dB (1 W, 1 m)   | 97 dB (1 W, 1 m)   | 99 dB (1 W, 1 m)   | 98 dB (1 W, 1 m)           | 101 dB (1 W, 1 m)          |
| Impedance:              | 8 ohms             | 8 ohms             | 8 ohms             | 8 ohms                     | 8 ohms                     |
| Frequency range:        | 20-400 Hz          | 20-300 Hz          | 20-300 Hz          | 20-400 Hz                  | 15-300 Hz                  |
| Dimensions (H x W x D): | 480 x 390 x 320 mm | 585 x 470 x 455 mm | 675 x 545 x 455 mm | 745 x 390 x 320 mm         | 900 x 465 x 455 mm         |
| Weight:                 | 12 kg              | 18 kg              | 29 kg              | 18 kg                      | 27 kg                      |