



ACTIVE

OMNITRONIC MagiCarpet 2-way active speaker
Active 2-way PA speaker system

- Active full-range party speaker system with 80-360 W RMS power
- 20/26/30/38 cm bass speaker (8-15") with 38/50/62 mm voice coil
- 25/34/44 mm titanium driver
- Equalizer for adjusting low and high frequencies
- LED power and clipping indicator
- Rugged wooden housing with black felt cover
- Impact-resistant steel grille, steel corners and support feet

- No. 11037401..... MagiCarpet-208A
- No. 11037402..... MagiCarpet-210A
- No. 11037403..... MagiCarpet-212A
- No. 11037404..... MagiCarpet-215A
- No. 11037405..... MagiCarpet-2215A

Technical specifications:

Device:	MagiCarpet-208A	MagiCarpet-210A	MagiCarpet-212A	MagiCarpet-215A	MagiCarpet-2215A
Power supply:	115/230 V AC, 50/60 Hz	115/230 V AC, 50/60 Hz	115/230 V AC, 50/60 Hz	115/230 V AC, 50/60 Hz	115/230 V AC, 50/60 Hz
Power consumption:	70 W (1/8 power)	70 W (1/8 power)	70 W (1/8 power)	100 W (1/8 Power)	100 W (1/8 Power)
Rated power:	80 W RMS	100 W RMS	150 W RMS	180 W RMS	180 W RMS
Program power:	160 W	160 W	300 W	360 W	360 W
Components:	20 cm woofer (8"), 25 mm horn	26 cm woofer (10"), 34 mm horn	30 cm woofer (12"), 34 mm horn	38 cm woofer (15"), 44 mm horn	2 x 38 cm woofer (15"), 44 mm horn
Input:					
Line:	6.3 mm jack, RCA L/R	6.3 mm jack, RCA	6.3 mm jack, RCA L/R	6.3 mm jack, RCA L/R	6.3 mm jack, RCA L/R
Mic:	2 x XLR, 6.3 mm jack, RCA L/R	2 x XLR, 6.3 mm jack, RCA L/R	2 x XLR, 6.3 mm jack, RCA L/R	2 x XLR, 6.3 mm jack	2 x XLR, 6.3 mm jack
Output:					
Line:	6.3 mm jack	6.3 mm jack	6.3 mm jack	6.3 mm jack	6.3 mm jack
Sensitivity:	88 dB (1 W, 1 m)	90 dB (1 W, 1 m)	92 dB (1 W, 1 m)	94 dB (1 W, 1 m)	96 dB (1 W, 1 m)
Frequency range:	65-18000 Hz	55-18000 Hz	50-18000 Hz	45-18000 Hz	45-18000 Hz
Dimensions (HxWxD):	340 x 380 x 655 mm	340 x 380 x 645 mm	410 x 415 x 680 mm	430 x 470 x 825 mm	430 x 470 x 1235 mm
Weight:	18 kg	19 kg	24 kg	31.5 kg	42.5 kg



151A

ACTIVE

OMNITRONIC MagiCarpet active subwoofer
Active bassreflex subwoofer

- With 200/250 W RMS power
- 38/45 cm bass speaker (15/18") with 76/100 mm voice coil
- Adjustable crossover frequency from 40 to 250 Hz
- Phase control
- Power and clipping indicator
- Rugged wooden housing with black felt cover
- Impact-resistant steel grille, steel corners and support feet

- No. 11037406..... MagiCarpet-151A
- No. 11037407..... MagiCarpet-181A



181A

Technical specifications:

Device:	MagiCarpet-208A	MagiCarpet-210A
Power supply:	115/230 V AC, 50/60 Hz	115/230 V AC, 50/60 Hz
Power consumption:	170 W (1/8 power)	170 W (1/8 power)
Rated power:	200 W RMS	250 W RMS
Program power:	400 W	500 W
Woofer:	38 cm (15")	46 cm (18")
Signal input:	combination XLR/6.3 mm jack L/R	combination XLR/6.3 mm jack L/R
Signal output:	XLR L/R	XLR L/R
Sensitivity:	96 dB (1 W, 1 m)	98 dB (1 W, 1 m)
Frequency range:	35-18000 Hz	35-18000 Hz
Crossover frequency:	40-250 Hz	40-250 Hz
Acoustic loading:	bassreflex	bassreflex
Dimensions (WxDxH):	445 x 500 x 635 mm	505 x 555 x 700 mm
Weight:	33 kg	43 kg

