



ACTIVE

OMNITRONIC KM Active stage monitor, coaxial

Active coaxial stage monitor

- Class D/AB biamp power amplifier
- Bassreflex cabinet provides high SPL
- Line input (XLR/6.3 mm jack)
- Parallel output (XLR) for linking further active speaker systems
- Low cut, volume control
- Dual limiter and overload protection
- Flange for stand installation

No. 11038035 KM-110A
 No. 11038036 KM-112A
 No. 11038037 KM-115A

Technical specifications:

Device:	KM-110A	KM-112A	KM-115A
Power supply:	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~
Power consumption:	80 W (1/8 power)	180 W (1/8 power)	300 W (1/8 power)
Rated power:	150 W RMS	300 W RMS	300 W RMS
Program power:	300 W	600 W	600 W
Components:	25 cm woofer (10"), 3.5 cm driver (1.35")	30 cm woofer (12"), 3.5 cm driver (1.35")	38 cm woofer (15"), 3.5 cm driver (1.35")
Input:	combination XLR/6.3 mm jack	combination XLR/6.3 mm jack	combination XLR/6.3 mm jack
Parallel output:	XLR	XLR	XLR
Frequency range:	60-20000 Hz	50-20000 Hz	45-20000 Hz
Max. SPL:	121 dB (1 m)	123 dB (1 m)	124 dB (1 m)
Dispersion angle (HxV):	80° x 80°	80° x 80°	60° x 60°
Dimensions (HxWxD):	420 x 480 x 300 mm	460 x 500 x 340 mm	510 x 600 x 370 mm
Weight:	11 kg	15 kg	18 kg



M-1020



M-1030



M-1230



M-1530

Technical specifications:

Device:	M-1220	M-1230	M-1520	M-1530
Rated power:	300 W RMS	300 W RMS	400 W RMS	400 W RMS
Program power:	600 W	600 W	800 W	800 W
Components:	30 cm woofer (12"), horn	30 cm woofer (12"), horn	38 cm woofer (15"), horn	38 cm woofer (15"), horn
Connections:	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets
Sensitivity:	96 dB (1 W, 1 m)	96 dB (1 W, 1 m)	97 dB (1 W, 1 m)	97 dB (1 W, 1 m)
Impedance:	8 ohms	8 ohms	8 ohms	8 ohms
Frequency range:	40 - 18000 Hz	40 - 18000 Hz	30 - 18000 Hz	30 - 18000 Hz
Dimensions (H x W x D):	395 x 615 x 275 mm	585 x 405 x 465 mm	480 x 665 x 335 mm	665 x 480 x 475 mm
Weight:	14 kg	18 kg	23 kg	24 kg

M Monitor 400W

2-way stage monitor

- Rugged 2-way speaker-system with 300/400 W RMS
- Large mid-range horn with coil-driver for balanced mids
- With passive 2-way crossover

No. 11038011 M-1220, 30 cm
 No. 11038012 M-1230, 30 cm
 No. 11038015 M-1520, 38 cm
 No. 11038016 M-1530, 38 cm