



### OMNITRONIC DS MK2 3-way speaker

Rugged full-range speaker system for PA and DJ applications

- Rugged full-range speaker system for PA and DJ applications
- Improved version with more power
- 3-way bass-reflex system
- 30 cm woofer (12"), horn, 2 tweeters
- Piezo super tweeter for powerful treble
- High-quality horn for smooth mid-range

No. 11037106 .....	DS-83 MK2
No. 11037111 .....	DS-103 MK2
No. 11037116 .....	DS-123 MK2
No. 11037121 .....	DS-153 MK2

#### Technical specifications:

Device:	DS-83	DS-103	DS-123	DS-153
Rated power:	150 W RMS	200 W RMS	250 W RMS	300 W RMS
Program power:	300 W	400 W	500 W	600 W
Components:	20 cm woofer (8"), horn, 2 tweeters	25 cm woofer (10"), horn, 2 tweeters	30 cm woofer (12"), horn, 2 tweeters	38 cm woofer (15"), horn, 3 tweeters
Connections:	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets
Sensitivity:	93 dB (1 W, 1 m)	94 dB (1 W, 1 m)	95 dB (1 W, 1 m)	96 dB (1 W, 1 m)
Impedance:	8 ohms	8 ohms	8 ohms	8 ohms
Frequency range:	50 - 20000 Hz	45 - 20000 Hz	40 - 20000 Hz	35 - 20000 Hz
Dimensions (H x W x D):	480 x 320 x 250 mm	550 x 370 x 280 mm	645 x 440 x 350 mm	750 x 510 x 360 mm
Weight:	8 kg	9.5 kg	14 kg	18 kg



### OMNITRONIC TX 3-way speaker

Full-Range speaker-system for disco or live music

- Tweeter with coil-driver for powerful treble
- Woofer: 30 cm (12"), 38 cm (15"), 2 x 38 cm (15") - horn, 1 to 2 tweeters (TX-2520)
- Powerful, dry bass
- Very high durability
- Cone-shaped form

No. 11037635 .....	TX-1220
No. 11037638 .....	TX-1520
No. 11037644 .....	TX-2520

### OMNITRONIC TMX 3-way speaker

Full-Range speaker-system for disco or live music

- With special, highly temperature resistant vibrating coil
- Tweeter with coil-driver for powerful treble
- Cone midrange speaker
- 30/38 cm woofer (12/15"), 15/20 cm woofer (6/8"), tweeter
- With passive 3-way crossover
- Very high durability

No. 11038571 .....	TMX-1230
No. 11038581 .....	TMX-1530

#### Technical specifications:

Device:	TMX-1230	TMX-1530	TX-1220	TX-1520	TX-2520
Rated power:	400 W RMS	500 W RMS	350 W RMS	450 W RMS	700 W RMS
Program power:	800 W	1000 W	700 W	900 W	1400 W
Components:	30 cm woofer (12"), 15 cm woofer (6"), tweeter	38 cm woofer (15"), 20 cm woofer (8"), tweeter	30 cm woofer (12"), horn, tweeter	38 cm woofer (15"), horn, tweeter	2 x 38 cm woofer (2 x 15"), horn, 2 tweeter
Connections:	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets
Sensitivity:	96 dB (1 W, 1 m)	97 dB (1 W, 1 m)	96 dB (1 W, 1 m)	97 dB (1 W, 1 m)	101 dB (1 W, 1 m)
Impedance:	8 ohms	8 ohms	8 ohms	8 ohms	8 ohms
Frequency response:	40 - 18000 Hz	30 - 18000 Hz	40 - 18000 Hz	30 - 18000 Hz	30 - 18000 Hz
Dimensions (H x W x D):	655 x 400 x 310 mm	755 x 490 x 370 mm	690 x 360 x 345 mm	800 x 455 x 360 mm	1155 x 460 x 385 mm
Weight:	14 kg	18 kg	14 kg	25 kg	34 kg