

OMNITRONIC KB Plastic cabinet speakers, active

- No. 11038692 KB-208A, 20 cm
- No. 11038694 KB-210A, 25 cm
- No. 11038696 KB-212A, 30 cm
- No. 11038698 KB-215A, 38 cm

- + 2-band EQ master signal
- + Large mid-range horn
- + 2-way crossover
- + Flange for stand installation
- + Incl. brackets for use as floor monitor (KB-210-215)

ACTIVE



KB-208A

KB-210A

KB-212A

KB-215A



KB-208A



KB-210-215A

- Large mid-range horn • 2-way crossover • Mic and line inputs with separate level controls • Master control with 2-way tone control and clip LED • Strong protective grille for perfect protection • Scratch-resistant plastic housing • Compact speaker-system for car transport • Flange for stand installation • Ideal for live music or for permanent installation in party rooms



Including monitor feet (not KBA-208/208A)



KB-210/KB-210A
KB-212/KB-212A
KB-215/KB-215A

Accessories:

Cable CC-30 2x2 RCA-plugs 3m HighEnd	No. 30209370
Cable MC-50, 5m, black, XLR m/f, balanced	No. 3022050N
Speaker system stand alu, black	No. 60004120
OMNITRONIC STS-100 Speaker stand w. crank	No. 60004150
EUROLITE STV-40A Lighting stand, alu	No. 59007001
EUROLITE STW-370A Winch-driven stand 370cm	No. 60000820
Wall-mounting for speakers with flange	No. 60004610
Wall-mounting XY for speakers with flange	No. 60004620

Technical specifications:	KB-208A	KB-210A	KB-212A	KB-215A
Product:	KB-208A	KB-210A	KB-212A	KB-215A
Power supply:	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~
Rated power:	80 W RMS	120 W RMS	150 W RMS	180 W RMS
Program power:	160 W	240 W	300 W	360 W
Components:	20 cm woofer (8"), 2.5 cm horn (1")	25 cm woofer (10"), 3.5 cm horn (1.35")	30 cm woofer (12"), 3.5 cm horn (1.35")	38 cm woofer (15"), 4.5 cm horn (1.75")
Inputs:				
1 Mic	XLR	XLR or balanced 6.3 mm jack	XLR or balanced 6.3 mm jack	XLR or balanced 6.3 mm jack
1 Line	XLR or RCA	XLR or RCA	XLR or RCA	XLR or RCA
Outputs:				
1 Line Out		XLR or balanced 6.3 mm jack	XLR or balanced 6.3 mm jack	XLR or balanced 6.3 mm jack
Max. SPL:	102 dB	110 dB	115 dB	120 dB
Impedance:		4 ohms	4 ohms	
Frequency range:	65 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz	40 Hz - 18 kHz
Dimensions (H x W x D):	400 x 277 x 257 mm	510 x 350 x 285 mm	580 x 480 x 325 mm	740 x 555 x 400 mm
Weight:	8 kg	14 kg	18 kg	27 kg