

OMNITRONIC KB Plastic cabinets

- No. 11038691 KB-208, 20 cm
- No. 11038693 KB-210, 25 cm
- No. 11038695 KB-212, 30 cm
- No. 11038697 KB-215, 38 cm

- + Large mid-range horn
- + 2-way crossover
- + Strong protective grille for perfect protection
- + Flange for stand installation



- Large mid-range horn • 2-way crossover • Speaker input and parallel 6.3 mm jack input/output • Flange for stand installation • Strong protective grille for perfect protection • Scratch-resistant plastic housing • Compact speaker-system for car transport • Ideal for live music or for permanent installation in party rooms



KB-208

KB-210-215

Accessories:

OMNITRONIC STS-100 Speaker stand w. crank	No. 60004150
EUROLITE STV-40A Lighting stand, alu	No. 59007001
EUROLITE STW-370A Winch-driven stand 370cm	No. 60000820
Wall-mounting for speakers with flange	No. 60004610
Wall-mounting XY for speakers with flange	No. 60004620

Technical specifications:	KB-208	KB-210	KB-212	KB-215
Product:	KB-208	KB-210	KB-212	KB-215
Rated power:	100 W RMS	250 W RMS	300 W RMS	350 W RMS
Program power:	200 W	500 W	600 W	700 W
Components:	20 cm woofer, 2.5 cm horn	25 cm woofer, 3.5 cm horn	30 cm woofer, 3.5 cm horn	38 cm woofer, 4.5 cm horn
Connections:	Speaker, Jack socket	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets
Sensitivity (1 W/m):	90 dB	92 dB	92 dB	95 dB
Max. SPL (1 m):	112 dB	120 dB	120 dB	123 dB
Impedance:	8 Ω	8 Ω	8 Ω	8 Ω
Frequency range:	65-18,000 Hz	55-18,000 Hz	50-18,000 Hz	40-18,000 Hz
Dimensions (H x W x D):	400 x 277 x 257 mm	515 x 430 x 305 mm	580 x 480 x 325 mm	740 x 555 x 400 mm
Weight:	6.5 kg	10 kg	18 kg	27 kg

OMNITRONIC NKB Plastic cabinets

- No. 11038780 NKB-208
- No. 11038783 NKB-210
- No. 11038786 NKB-212
- No. 11038789 NKB-215

- + 2-way speaker system for PA and DJ applications
- + Bass reflex system
- + Stable plastic cabinet
- + Flange for stand installation
- + Handles



- 2-way bass-reflex system with 20 cm woofer and 2.5 cm tweeter • Speaker connections • Stable plastic housing with protective grille and handles • Flange for stand installation • Can be used as floor monitor, standing, on a speaker stand or wall holder • For mobile live and DJ applications



Technical specifications:	NKB-208	NKB-210	NKB-212	NKB-215
Product:	NKB-208	NKB-210	NKB-212	NKB-215
Rated power:	90 W RMS	140 W RMS	160 W RMS	200 W RMS
Program power:	180 W	300 W	380 W	450 W
Components:	20 cm woofer (8"), 2.5 cm horn (1")	25 cm woofer (10"), 3.5 cm horn (1.35")	30 cm woofer (12"), 3.5 cm horn (1.35")	38 cm woofer (15"), 4.4 cm horn (1.73")
Connections:	2 x speaker	2 x speaker	2 x speaker	2 x speaker
Sensitivity:	95 dB (1 W, 1 m)	97 dB (1 W, 1 m)	97 dB (1 W, 1 m)	103 dB (1 W, 1 m)
Max. SPL:	112 dB (1 m)	120 dB (1 m)	120 dB (1 m)	123 dB (1 m)
Impedance:	8 ohms	8 ohms	8 ohms	8 ohms
Frequency range:	60 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz	45 Hz - 18 kHz
Dimensions (HxWxD):	400 x 255 x 220 mm	515 x 320 x 290 mm	592 x 405 x 320 mm	710 x 485 x 380 mm
Weight:	6 kg	10 kg	18 kg	20 kg