



OMNITRONIC VFM 2-way speaker

Passive 2-way speaker system for PA and DJ applications

- 2-way bass-reflex system
- Speaker connections
- Stable plastic housing with protective grille and handles
- Flange for stand installation

| | |
|--------------------|---------|
| No. 11038765 | VFM-208 |
| No. 11038768 | VFM-210 |
| No. 11038771 | VFM-212 |
| No. 11038774 | VFM-215 |

ACTIVE

OMNITRONIC VFM A 2-way speaker, active

Active 2-way speaker system for PA and DJ applications

- Class A/B circuitry: optimum sound and power
- Flange for stand installation
- 2 wheels for easy transport - for model 212/215 only

| | |
|--------------------|----------|
| No. 11038766 | VFM-208A |
| No. 11038769 | VFM-210A |
| No. 11038772 | VFM-212A |
| No. 11038775 | VFM-215A |

ACTIVE MP3 USB SDHC BLUETOOTH

OMNITRONIC VFM AP 2-way speaker, active

Active 2-way speaker system for PA and DJ applications

- AP versions with audio player, SD card slot, USB input
- Stream music wirelessly from your mobile devices (e.g. smartphone, tablet) via Bluetooth - for AP versions only
- Class A/B circuitry: optimum sound and power
- Flange for stand installation
- 2 wheels for easy transport - for model 212/215 only

| | |
|--------------------|-----------|
| No. 11038767 | VFM-208AP |
| No. 11038770 | VFM-210AP |
| No. 11038773 | VFM-212AP |
| No. 11038776 | VFM-215AP |

Technical specifications:

| Device: | VFM-208 | VFM-210 | VFM-212 | VFM-215 |
|---------------------|--|---|---|---|
| Rated power: | 80 W RMS | 90 W RMS | 140 W RMS | 150 W RMS |
| Program power: | 160 W | 180 W | 280 W | 300 W |
| LF speaker: | 20 cm bass/mids (8") with 40 mm voice coil | 25 cm bass/mids (10") with 40 mm voice coil | 30 cm bass/mids (12") with 40 mm voice coil | 38 cm bass/mids (15") with 50 mm voice coil |
| HF speaker: | 25 mm compression driver (1") | 25 mm compression driver (1") | 25 mm compression driver (1") | 25 mm compression driver (1") |
| Connections: | 2 x Speaker | 2 x Speaker | 2 x Speaker | 2 x Speaker |
| Max. SPL: | 111 dB (1 m) | 115 dB (1 m) | 120 dB (1 m) | 122 dB (1 m) |
| Impedance: | 8 ohms | 8 ohms | 8 ohms | 8 ohms |
| Frequency range: | 75 Hz - 20 kHz | 65 Hz - 20 kHz | 50 Hz - 20 kHz | 45 Hz - 20 kHz |
| Dimensions (HxWxD): | 438 x 295 x 245 mm | 545 x 360 x 295 mm | 740 x 480 x 395 mm | 740 x 480 x 395 mm |
| Weight: | 5.5 kg | 7 kg | 10 kg | 15 kg |

Technical specifications:

| Device: | VFM-208A/AP | VFM-210A/AP | VFM-212A/AP | VFM-215A/AP |
|---------------------|--|---|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz | 100-240 V AC, 50/60 Hz | 100-240 V AC, 50/60 Hz | 100-240 V AC, 50/60 Hz |
| Rated power: | 80 W RMS | 90 W RMS | 140 W RMS | 150 W RMS |
| Program power: | 160 W | 180 W | 280 W | 300 W |
| LF speaker: | 20 cm bass/mids (8") with 40 mm voice coil | 25 cm bass/mids (10") with 40 mm voice coil | 30 cm bass/mids (12") with 40 mm voice coil | 38 cm bass/mids (15") with 50 mm voice coil |
| HF speaker: | 25 mm compression driver (1") | 25 mm compression driver (1") | 25 mm compression driver (1") | 25 mm compression driver (1") |
| Mic: | combination XLR/6.3 mm jack | combination XLR/6.3 mm jack | 2 x 3-pin XLR or 6.3 mm jack, unbal. | 2 x 3-pin XLR or 6.3 mm jack, unbal. |
| 1 Line: | stereo RCA | stereo RCA | stereo RCA | stereo RCA |
| Outputs: | | | | |
| 1 Line: | stereo RCA | stereo RCA | stereo RCA | stereo RCA |
| Max. SPL: | 111 dB (1 m) | 115 dB (1 m) | 120 dB (1 m) | 122 dB (1 m) |
| Frequency range: | 75 Hz - 20 kHz | 65 Hz - 20 kHz | 50 Hz - 20 kHz | 45 Hz - 20 kHz |
| Dimensions (HxWxD): | 438 x 295 x 245 mm | 545 x 360 x 295 mm | 630 x 420 x 342 mm | 740 x 480 x 395 mm |
| Weight: | 5.5 kg | 7 kg | 10 kg | 15 kg |