

OMNITRONIC NKB Plastic cabinets, active

- No. 11038781 NKB-208A
- No. 11038784 NKB-210A
- No. 11038787 NKB-212A
- No. 11038790 NKB-215A

- + Active 2-way speaker system for PA and DJ applications
- + 2-way bass-reflex system with 30 cm woofer and 3.5 cm tweeter
- + Mic and line inputs with separate level controls
- + Class D circuitry

- 2-way bass-reflex system with woofer and tweeter
- Mic and line inputs with separate level controls
- Master control with 2-way tone control and clip LED
- Line output for linking further active speaker systems
- Front blue signal LED
- Stable plastic housing with protective grille and handles
- Flange for stand installation
- Can be used as floor monitor, standing, on a speaker stand or wall holder
- For mobile live and DJ applications

ACTIVE



NKB-208A

NKB-210A

NKB-212A

NKB-215A



Technical specifications:	NKB-208A	NKB-210A	NKB-212A	NKB-212AP	NKB-215A	NKB-215AP
Product:	NKB-208A	NKB-210A	NKB-212A	NKB-212AP	NKB-215A	NKB-215AP
Power supply:	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~
Rated power:	90 W RMS	120 W RMS	200 W RMS	200 W RMS	200 W RMS	200 W RMS
Program power:	180 W	200 W	300 W	300 W	300 W	300 W
Components:	20 cm woofer (8"), 2.5 cm horn (1")	25 cm woofer (10"), 3.5 cm horn (1.35")	30 cm woofer (10"), 3.5 cm horn (1.35")	30 cm woofer (10"), 3.5 cm horn (1.35")	38 cm woofer (15"), 4.4 cm horn (1.73")	38 cm woofer (15"), 4.4 cm horn (1.73")
Storage media:				USB devices and SD(HC) cards		USB devices and SD(HC) cards
Inputs:						
1 Mic:	3-pin XLR or 6.3 mm jack, unbalanced	3-pin XLR or 6.3 mm jack, unbalanced	3-pin XLR or 6.3 mm jack, unbalanced	3-pin XLR or 6.3 mm jack, unbalanced	3-pin XLR or 6.3 mm jack, unbalanced	3-pin XLR or 6.3 mm jack, unbalanced
1 Line:	XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA
Outputs:						
1 Line:	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.
Max. SPL:	105 dB (1 m)	114 dB (1 m)	117 dB (1 m)	114 dB (1 m)	120 dB (1 m)	120 dB (1 m)
Frequency range:	60 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz	50 Hz - 18 kHz	40 Hz - 18 kHz	40 Hz - 18 kHz
Dimensions (HxWxD):	400 x 255 x 220 mm	515 x 320 x 290 mm	592 x 405 x 320 mm	592 x 405 x 320 mm	710 x 485 x 380 mm	710 x 485 x 380 mm
Weight:	8 kg	12 kg	20 kg	20 kg	22 kg	22 kg