



NKB-208A

NKB-208AP



ACTIVE MP3 SD^{HC} USB

OMNITRONIC NKB Plastic cabinet, activ

Active 2-way speaker system for PA and DJ applications

- Built-in MP3 player with SD card slot and USB input
- 2-way bass-reflex system
- 20 - 38 cm woofer (8 - 15") and 2.5 - 4.4 cm tweeter (1 - 1.73")
- Low weight due to class D circuitry (NKB-210-215)
- Perfect for mobile use
- 1 x line, 1 x mic with separate level controls
- 2-band EQ
- Flange

No. 11038781.....	NKB-208A
No. 11038782.....	NKB-208AP
No. 11038784.....	NKB-210A
No. 11038785.....	NKB-210AP
No. 11038787.....	NKB-212A
No. 11038788.....	NKB-212AP
No. 11038790.....	NKB-215A
No. 11038791.....	NKB-215AP

Technical specifications:

Device:	NKB-208A	NKB-208AP	NKB-210A	NKB-210AP	NKB-212A	NKB-212AP	NKB-215A	NKB-215AP
Power supply:	230 V AC, 50 Hz ~	230 V AC, 50 Hz ~	115/250 V AC, 50/60 Hz ~	115/250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~	90-250 V AC, 50/60 Hz ~
Rated power:	90 W RMS	90 W RMS	120 W RMS	120 W RMS	200 W RMS	200 W RMS	200 W RMS	200 W RMS
Program power:	180 W	180 W	200 W	200 W	300 W	300 W	300 W	300 W
Components:	20 cm woofer (8"), 2.5 cm horn (1")	20 cm woofer (8"), 2.5 cm horn (1")	25 cm woofer (10"), 3.5 cm horn (1.35")	25 cm woofer (10"), 3.5 cm horn (1.35")	30 cm woofer (10"), 3.5 cm horn (1.35")	30 cm woofer (10"), 3.5 cm horn (1.35")	38 cm woofer (15"), 4.4 cm horn (1.73")	38 cm woofer (15"), 4.4 cm horn (1.73")
Storage media:		USB devices and SD(HC) cards		USB devices and SD(HC) cards		USB devices and SD(HC) cards		USB devices and SD(HC) cards
Inputs:								
1 Mic:	6.3 mm jack	6.3 mm jack	3-pin XLR or 6.3 mm jack	3-pin XLR or 6.3 mm jack	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.
1 Line:	6.3 mm jack or stereo RCA	6.3 mm jack or stereo RCA	3-pin XLR or stereo RCA	3-pin XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA	XLR or stereo RCA
Outputs:								
1 Line:	6.3 mm jack	6.3 mm jack	6.3 mm jack	6.3 mm jack	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.	3-pin XLR or 6.3 mm jack, unbal.
Max. SPL:	105 dB (1 m)	105 dB (1 m)	114 dB (1 m)	114 dB (1 m)	117 dB (1 m)	114 dB (1 m)	120 dB (1 m)	120 dB (1 m)
Frequency range:	60 Hz - 18 kHz	60 Hz - 18 kHz	55 Hz - 18 kHz	55 Hz - 18 kHz	50 Hz - 18 kHz	50 Hz - 18 kHz	40 Hz - 18 kHz	40 Hz - 18 kHz
Dimensions (HxWxD):	400 x 255 x 220 mm	400 x 255 x 220 mm	515 x 320 x 290 mm	515 x 320 x 290 mm	592 x 405 x 320 mm	592 x 405 x 320 mm	710 x 485 x 380 mm	710 x 485 x 380 mm
Weight:	8 kg	8 kg	12 kg	12 kg	14 kg	14 kg	22 kg	20 kg