



ACTIVE

OMNITRONIC AS-800 Active system

Convincing compact active PA system, 800 watts RMS

- Mobile subwoofer/satellite system with class D circuitry (800 watts RMS)
- Provides perfect sound and good level stability - ideal for solo entertainers, small bands and mobile discos, up to medium-sized party events
- Microphone input (combo XLR/6.3 mm jack)
- Aux input (3.5 mm jack/RCA), ideal for portable music players (e.g. iPod)
- 5-band equalizer for fine-tuned sound of the master signal
- Adjustable crossover frequency for subwoofer and satellites
- PowerCon input, power cable included



No. 11038814

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption (max.):	900 W
Power output sine:	
Subwoofer:	500 W RMS
Satellite speakers:	2 x 150 W RMS
Components:	
Subwoofer:	38 cm woofer (15")
Satellite speakers:	2 x 20 cm woofer (8"), 2 x 8 cm titanium tweeter (3.2")
Sensitivity:	
Subwoofer:	96 dB (1 W, 1 m)
Satellite speakers:	94 dB (1 W, 1 m)
Max. SPL:	
Subwoofer:	123 dB (1 m)
Satellite speakers:	114 dB (1 m)
Frequency range:	
Subwoofer:	35 - 140 Hz
Satellite speakers:	140 Hz - 20 kHz
Inputs:	
Line:	combination XLR/6.3 mm jack L/R
Aux:	3.5 mm jack/stereo RCA
Mic:	combination XLR/6.3 mm jack
Outputs:	
Line:	XLR L/R (feed-through output)
Speaker:	2 x Speaker, 8 ohms
Protection circuits:	Short-circuit, overheat, overload, overcurrent
Dimensions (LxWxH):	
Subwoofer:	702 x 450 x 495 mm
Satellite speakers:	261 x 273 x 438 mm
Total weight:	60 kg

ACTIVE

OMNITRONIC AR-212A 2-way speaker

Active 2-way speaker system for PA and DJ applications, 550 W max.

- Active full-range system with class D circuitry
- 2-channel power amplifier with integrated active crossover network
- 2-way system, 550 W max.
- 2 x 30 cm subwoofer in bassreflex cabinet
- 12 cm titanium driver system



No. 11038840

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz ~
Power consumption (max.):	650 W
LF amplifier:	500 W max.
HF amplifier:	50 W max.
Components:	2 x 30 cm woofer (12"), 11.5 cm horn (4.5")
Line input:	combination XLR/6.3 mm jack
Microphone input:	combination XLR/6.3 mm jack
Line output:	XLR (parallel output)
Frequency range:	40 Hz - 20 kHz
Dimensions (H x W x D):	900 x 410 x 385 mm
Weight:	31 kg