

ACTIVE

OMNITRONIC ASS Active system

Powerful mobile column PA system

- With column top speaker and active subwoofer with class D circuitry
- Ultra-compact, extremely light - this system can be installed and setup in time
- Convinces with excellent speech reproduction and wide coverage
- Bassreflex subwoofer: 2 x 25 cm (10") or 38 cm (15")
- Fullrange column speaker with 12/8 x 8 cm drivers (3")

No. 11038851ASS-1503
 No. 11038852ASS-1023
 No. 11038857Castor set for ASS-1503



Technical specifications:

Device:	ASS-1023	ASS-1503
Power supply:	115/230 V AC, 50/60 Hz ~	115/230 V AC, 50/60 Hz ~
Power consumption (max.):	200 VA (1/8 power)	200 VA (1/8 power)
Power output sine:		
Subwoofer:	400 W RMS	500 W RMS
Satellite speaker:	200 W RMS	350 W RMS
Components:		
Subwoofer:	2 x 25 cm woofer (10")	38 cm woofer (15")
Satellite speaker:	8 x 8 cm woofer (8 x 3"),	12 x 8 cm woofer (12 x 3"),
Max. SPL:		
Subwoofer:	120 dB (1 m)	122 dB (1 m)
Satellite speaker:	118 dB (1 m)	121 dB (1 m)
Frequency range:		
Subwoofer:	45 - 180 Hz	45 - 180 Hz
Satellite speaker:	120 Hz - 20 kHz	120 Hz - 20 kHz
Crossover frequency:	40 - 160 Hz	40 - 160 Hz
Line input:	combination XLR/6.3 mm jack, bal. and RCA L/R	combination XLR/6.3 mm jack, bal. and RCA L/R
Mic input:	combination XLR/6.3 mm jack, bal.	combination XLR/6.3 mm jack, bal.
Speaker output:	1 x speaker, 4 ohms	1 x speaker, 4 ohms