

OMNITRONIC PAM-500 MK2 Active PA system

No. 11038892

- + 6-channel power mixer
- + 2 speaker boxes
- + MP3 player
- + FM/AM tuner
- + 2 microphones

ACTIVE

MP3

USB



- PA system with 6-channel mixer, power amplifier, 2 full-range speaker systems and 2 dynamic microphones
- Integrated FM/AM tuner and MP3 player with USB input
- Easy transportation via 4 wheels (2 of which with brake) and telescopic trolley-handle
- The system includes all components needed for seminars, conferences, presentations, trade shows, fashion shows, solo entertainers, weddings, sales booths, aerobics etc.
- Delivery includes all cables: 2 XLR-XLR microphone cables, 2 jack-jack speaker cables, power cable
- 4 mono input channels mic/line, one of which with adjustable priority circuit for automatic attenuation of the other channels
- 2 stereo inputs for line signal sources, e.g. for CD players or multimedia applications from laptops
- Each channel with adjustable digital reverb, 3-band EQ, balance/pan, level
- 10-band equalizer for fine-tuned sound of the master signal
- Stereo master control for adjusting the output level and for balance control
- Aux send and aux return jacks for monitoring or for inserting external effectors
- Preamp master send and master return for inserting an external equalizer
- Stereo operation switchable to dual mono operation, allows for separately controllable monitor output (mono)
- Recording output independent of the master level
- Four 15 cm full-range speakers (6") per speaker system
- Bass-reflex system
- Impact-resistant steel grille
- Speaker flange for installation on a speaker stand or wall holder
- Power amplifier with latest switch mode power supply
- High efficiency, operation via safety power outlet
- Voltage selector for power supply adaption between 100 and 240 Volts
- Power supply with softstart

Technical specifications:

<i>General:</i>	
Power supply:	115/230 V AC, 50/60 Hz ~
Power consumption (max.):	150 W
Components:	4 x 15 cm speaker (4 x 6")
Dimensions (H x W x D):	760 x 845 x 330 mm
Weight:	30 kg
<i>Control unit:</i>	
<i>Inputs:</i>	
4 mono	XLR or balanced 6.3 mm jacks
2 stereo	RCA or 6.3 mm jacks
1 Aux Return	balanced 6.3 mm jack
Footswitch	6.3 mm jack
<i>Outputs:</i>	
2 Main Mix Out	balanced 6.3 mm jacks
1 Aux Send	balanced 6.3 mm jack
Rec Out	RCA
<i>Amplifier:</i>	
Nominal power output:	60 W RMS / 4 ohms
Maximum power output:	120 W / 4 ohms
Distortion:	0.05 %
S/N ratio:	>80 dB
Frequency range:	20-20000 Hz; ± 1 dB
Tuner channel:	FM 87 - 108 Hz AM 522 - 1,620 Hz
MP3 player:	supports MP3 and WMA

OMNITRONIC COMBO-75 Active PA system

No. 11038897

- + Mixer/amplifier unit for mobile use
- + Two 150 W speakers
- + 4 mono input channels with gain and 2-band EQ
- + Digital reverb
- + 1 x Aux In

ACTIVE



- Portable PA system for mobile use, ideal for rental companies
- Two 150 W speakers
- Low-noise 4-channel mic/line mixer and amplifier integrated into a wooden housing with black plastic cover, handle and speaker-flange for installation on a speaker-stand or wall-mounting
- Amplifier output power 75 W RMS / 4 ohms
- 4 bal. mono input channels (XLR and 6.3 mm jack) with gain control, 2-band EQ and digital reverb
- 1 adjustable line input (stereo RCA) e.g. CD and MP3 players or for multimedia applications from PC and laptop
- Adjustable effect way for controlling external effect units (aux send/return)
- Master section with level control, 2-band EQ and reverb control
- 2 systems can be interconnected for stereo operation

Technical specifications:

<i>Mixer unit:</i>	
Power supply:	115/230 V AC, 50/60 Hz ~
Power consumption (max.):	150 W
Dimensions:	480 x 255 x 135 mm
Weight:	8 kg
<i>Inputs:</i>	
4 x mono mic/line (XLR/6.3 mm jack, bal.)	
1 x line (stereo RCA)	
1 x aux return (6.3 mm jack, bal.)	
1 x aux send (6.3 mm jack, bal.)	
<i>Outputs:</i>	
2 x speaker out (Speaker)	
<i>Amplifier unit:</i>	
Nominal power output:	75 W RMS / 4 ohms
Maximum power output:	150 W / 4 ohms
Distortion:	0.85 %
S/N ratio:	>90 dB
Frequency range:	30 Hz - 20 kHz
<i>Loudspeakers:</i>	
Rated power:	100 W RMS
Program power:	150 W
Components:	25 cm woofer (10"), 2 cm horn (0.8")
Sensitivity (1 W/m):	93 dB
Impedance:	8 ohms
Frequency range:	65 Hz - 18 kHz
Dimensions:	530 x 370 x 277 mm
Weight:	9.5 kg (piece)

Accessories:

Speaker-cable 5m PROFI 2x1.5mm ²	No. 3022110M
Speaker stand BASIC, set w. 2 pcs	No. 60004020
Cable SKC-15 3.5mm jack pl.st/2xRCA 1,5m	No. 30225151