



www.omnitronic.com

OMNITRONIC PAS-208 II 2-Wege Top, 8" Best.-Nr. 11039420



2-Wege Multifunktionsbox

- Robustes Full-Range Topteil in stabilem Holzgehäuse
- Trapezförmiges Gehäuse zur vereinfachten Clustermontage
- Mit Flugvorrichtung zur hängenden Installation
- Mit passiver 2-Wege-Frequenzweiche
- Für Anwendungen, die im Bassbereich mehr Druck verlangen, empfehlen wir die Kombination mit PAS-Subwoofern
- Ausgeglichener Frequenzgang mit gewaltigem Schalldruck
- Gehäuse aus mehrschichtigem, 18 mm starkem Multiplex-Birkenholz
- Strapazierfähiger Strukturlack
- Ballwurfsicheres Metallgitter mit Akustikschaumstoff
- Einsatz stehend, auf Bassbox, auf Boxenhochständer bzw. Stativ oder fliegend
- Mit Einbaufansch zur Montage auf Boxenhochständer etc.
- Kompaktbox zum Transport im PKW
- Als PA-Boxen und Beschallungsanlagen für kleine bis mittlere Diskotheken gut geeignet

Technische Daten:

Belastbarkeit nominal: 150 W RMS
Belastbarkeit Programm: 300 W
Komponenten: 8" Woofer, 1" Horn
Anschlüsse: 2 Speaker-Buchsen
Empfindlichkeit: 97 dB (1 W, 1 m)
Max. Schalldruck: 122 dB (1 m)

Impedanz: 8 Ohm
Frequenzbereich: 70 Hz - 20 kHz
Abstrahlwinkel (1 kHz): 90° x 40°
Maße (H x B x T): 400 x 250 x 250 mm
Gewicht: 9 kg





www.omnitronic.com

OMNITRONIC PAS-208 II 2-way top, 8" **No. 11039420**



2-way multi-function speaker-system

- Rugged full-range top speaker in a stable wooden housing
- Trapezoidal housing shape for easy clustering
- Qualified for suspended installation
- With passive 2-way crossover
- For applications requiring enhanced bass punch, we recommend a combination with the PAS-subwoofers
- Balanced frequency range with high sound-pressure
- Housing made of several layer, 18-mm birch plywood
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Can be used standing, on a subwoofer, on a speaker-stand or stand or suspended
- With flange for speaker-stand installation etc.
- Compact speaker-system for car transport
- Ideal as PA-system or amplification system for small and medium-sized discotheques

Technical specifications:

Rated power: 150 W RMS
Program power: 300 W
Components: 8" woofer, 1" horn
Connections: 2 Speaker-sockets
Sensitivity (1 W/m): 97 dB
Max. SPL (1 m): 122 dB

Impedance: 8 Ohms
Frequency range: 70 Hz - 20 kHz
Dispersion angle (1 kHz): 90° x 40°
Dimensions (H x W x D): 400 x 250 x 250 mm
Weight: 9 kg

