



OMNITRONIC PAS II 2-way top

2-way multi-function speaker-system

- Qualified for suspended installation
- With passive 2-way crossover
- Rotatable constant directivity horn
- 25 cm woofer (10"), 2.5 cm horn (1")

No. 11039420.....	PAS-208 II, 20 cm
No. 11039421.....	PAS-228 II, 2x20 cm
No. 11039422.....	PAS-210 II, 25 cm
No. 11039424.....	PAS-212 II, 30 cm
No. 11039426.....	PAS-215 II, 38 cm

Technical specifications:

Device:	PAS-208 II	PAS-228	PAS-210 II	PAS-212 II	PAS-215 II
Rated power:	150 W RMS	180 W RMS	200 W RMS	300 W RMS	400 W RMS
Program power:	300 W	360 W	400 W	600 W	800 W
Components:	20 cm woofer (8"), 2.5 cm horn (1")	2 x 20 cm Woofer (2 x 8"), 2 x 8 cm Tweeter (2 x 3")	25 cm woofer (10"), 2.5 cm horn (1")	30 cm woofer (12"), 2.5 cm horn (1")	38 cm woofer (15"), 2.5 cm horn (1")
Connections:	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets
Sensitivity (1 W/m):	97 dB	93 dB (1 W, 1 m)	97 dB	98 dB	99 dB
Max. SPL (1 m):	122 dB	115 dB (1 m)	123 dB	125 dB	127 dB
Impedance:	8 ohms	4 Ohm	8 ohms	8 ohms	8 ohms
Frequency range:	70 Hz - 20 kHz	67 Hz - 18 kHz	60 Hz - 20 kHz	58 Hz - 20 kHz	50 Hz - 20 kHz
Dispersion angle (1 kHz):	90° x 40°		50-100° x 55°	50-100° x 55°	50-100° x 55°
Dimensions (H x W x D):	400 x 250 x 250 mm	355 x 490 x 340 mm	530 x 325 x 295 mm	620 x 375 x 400 mm	695 x 440 x 410 mm
Weight:	9 kg	14 kg	17.5 kg	25 kg	28 kg



OMNITRONIC PAS RO 2-way top

2-way speaker system for PA applications

- Passive full-range PA speaker
- 2-way bass-reflex system
- Rotatable constant directivity horn
- 25 - 38 cm woofer (10 - 15"), 2.5 cm horn (1")
- Passive 2-way crossover
- PTC tweeter protection
- Applicable for monitor use

No. 11039442.....	PAS-210 PRO
No. 11039444.....	PAS-212 PRO
No. 11039446.....	PAS-215 PRO



Technical specifications:

Device:	PAS-210 PRO	PAS-212 PRO	PAS-215 PRO
Rated power:	250 W RMS	300 W RMS	400 W RMS
Program power:	500 W	600 W	800 W
Components:	25 cm woofer (10"), 2.5 cm horn (1")	30 cm woofer (12"), 2.5 cm horn (1")	38 cm woofer (15"), 2.5 cm horn (1")
Connections:	2 Speaker sockets	2 Speaker sockets	2 Speaker sockets
Sensitivity (1 W/m):	96 dB	97 dB	97 dB
Max. SPL (1 m):	120 dB	122 dB	124 dB
Impedance:	8 ohms	8 ohms	8 ohms
Frequency range:	65 Hz - 20 kHz	60 Hz - 20 kHz	55 Hz - 20 kHz
Crossover frequency:	2 kHz	2 kHz	2 kHz
Dispersion angle (1 kHz):	50-100° x 55°	50-100° x 55°	50-100° x 55°
Dimensions (HxWxD):	540 x 280 x 320 mm	600 x 355 x 330 mm	700 x 430 x 365 mm
Weight:	13 kg	16 kg	21 kg