

OMNITRONIC PAS-15 Subwoofer, 15" Best.-Nr. 11039610



15" Subwoofer

- Leistungsfähiger 2-Kammer Bandpass Subwoofer
- Quaderförmige Gehäuseform
- Zur Kombination mit PAS-Toppteilen
- Gewaltiger Schalldruck
- Sehr hohe Belastbarkeit
- Gehäuse aus mehrschichtigem, 18 mm starkem Multiplex-Birkenholz
- Strapazierfähiger Strukturlack
- Ballwurfsicheres Metallgitter mit Akustikschaumstoff
- Einsatz liegend oder stehend
- Mit zwei Einbaufanschen zur Montage des Toppteils
- Durch Einsatz mehrerer PAS-Boxen und entsprechender Endstufen lassen sich sehr große Beschallungsanlagen aufbauen
- Als PA-Boxen und Beschallungsanlagen für mittlere bis große Diskotheken gut geeignet

Technische Daten:

Belastbarkeit nominal:	600 W RMS	Max. Schalldruck:	124 dB (1 m)
Belastbarkeit Programm:	1200 W	Impedanz:	8 Ohm
Komponenten:	15" Woofer	Frequenzbereich:	38 - 500 Hz
Anschlüsse:	2 Speaker-Buchsen	Maße (H x B x T):	485 x 740 x 530 mm
Empfindlichkeit:	96 dB (1 W, 1 m)	Gewicht:	42 kg





www.omnitronic.com

OMNITRONIC PAS-15 Subwoofer, 15" No. 11039610



15" subwoofer

- Powerful 2-chamber bandpass subwoofer
- Cubic housing
- For a combination with the PAS-tops
- High sound-pressure
- Very high durability
- Housing made of several layer, 18-mm birch plywood
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Can be used lying or standing
- With two flanges for top speaker installation
- Very large amplification systems can be realized via several PAS-speaker-systems and the respective power amplifiers
- Ideal as PA-system or amplification system for medium-sized and large discotheques

Technical specifications:

Rated power: 600 W RMS
Program power: 1200 W
Components: 15" woofer
Connections: 2 Speaker-sockets
Sensitivity (1 W/m): 96 dB

Max. SPL (1 m): 124 dB
Impedance: 8 Ohms
Frequency range: 38 - 500 Hz
Dimensions (H x W x D): 485 x 740 x 530 mm
Weight: 42 kg

