



Technical specifications:

Device:	PAS-151A	PAS-181A
Power supply:	230 V AC, 50 Hz	230 V AC, 50 Hz
Power consumption:	670 W (1/8 power)	670 W (1/8 power)
Rated power:	500 W RMS	600 W RMS
Program power:	1000 W	1200 W
Woofer:	38 cm (15")	45 cm (18")
Signal input:	XLR L/R	XLR L/R
Signal output:	XLR L/R	XLR L/R
Sensitivity (1 W/m):	96 dB	96 dB
Max. SPL (1 m):	126 dB	126 dB
Frequency range:	45-120 Hz	40-120 Hz
Crossover frequency:	80-200 Hz	80-200 Hz
Acoustic loading:	bassreflex	bassreflex
Amplifier:	Class D	Class D
Dimensions (WxDxH):	680 x 460 x 590 mm	800 x 560 x 690 mm
Weight:	40 kg	50 kg

ACTIVE DSP

OMNITRONIC PAS PRO-DSP active subwoofer Pro active PA subwoofer

- High-power bassreflex subwoofer for permanent installations and touring purposes
- Housing made of 18 mm plywood multilayered glued
- 1000/1200 W Class D power amplifier with switch mode power supply
- 38/45 cm (15/18") bass speaker
- DSP-controlled limiter
- Phase reversal switch

No. 11039630 PAS-151A
No. 11039631 PAS-181A

