



PSSO CSA-115CXB Subwoofer

Compact speaker array subwoofer

- Bassreflex subwoofer
- 38 cm woofer (15")
- Selector switch for bi-amping operation
- Parallel Speaker connectors
- Stackable
- Flange

Technical specifications:

Rated power:	400 W RMS
Program power:	800 W
Components:	38 cm woofer (15")
Connections:	2 x Speakon (input/output) 1 x Speakon (top speaker)
Max. SPL (1 m):	123 dB
Impedance:	8 ohms
Frequency range:	40 Hz - 120 Hz
Crossover frequency:	120 Hz
Dimensions (H x W x D):	610 x 410 x 645 mm
Weight:	35 kg

No. 11040808black
No. 11040809white



ACTIVE

PSSO CSA-115CXA Active subwoofer black

Pro active PA subwoofer, 1000 W

- High-power bassreflex subwoofer for permanent installations and touring purposes
- High-performance Class D power amplifier with switch mode power supply
- XLR line output with high-pass filter (100 Hz) for the active top speakers CSA-218A and CSA-228A
- PowerCon mains input with parallel output for power supply of one top speaker (CSA-218A/CSA-228A)
- Limiter and protection set against short-circuit, overheat and overload



No. 11040819

Technical specifications:

Rated power:	1000 W
Components:	LF: 38 cm (15")
Frequency range:	35 Hz - 95 Hz
Crossover frequency:	HPF: 30 Hz, LPF: 100 Hz
Dispersion angle (HxV):	-
Maximum SPL:	123 dB
Acoustic loading:	Bassreflex
Cabinet material:	MDF (18 mm)
Amplifier:	Class D
THD:	<0.1 %
S/N ratio:	>80 dB
Damping factor:	>50
Input sensitivity:	2 V
Input impedance:	40 kohms/20 kohms (bal./unbal.)
Signal input:	XLR
Signal output:	XLR (HPF 100 Hz)
Power supply:	230 V AC, 50 Hz
Power consumption:	1000 W
Protection circuits:	Limiter, overheat, overload, short-circuit
LED indicators:	Power, signal, clip
Weight:	37 kg