

ItemNo. 11040900

**PSSO CLA-228 LINE ARRAY top, 2x8"**


**Year of construction: 2009**



11040900X18NXS00010001

**PSSO**<sup>®</sup>

**CLA-228 Compact Line Array Top**



**INPUT**

**WIRING**

Input:


1 +/- = MF +/-

2 +/- = HF +/-

Link:

1 +/- = MF +/-

2 +/- = HF +/-



**LINK**

MF/HF Rated power: 300/60 W RMS  
MF/HF Program power: 600/120 W  
Components: 2x8" woofer, 1x 1.73" driver  
MF/HF Sensitivity (1 W/m): 96/104 dB  
MF/HF Max. SPL (1 m): 120/121 dB  
Impedance: MF 16 Ohms / HF 16 Ohms  
Frequency range: 80 Hz - 18 kHz  
Crossover frequency: 1.3 kHz  
Dispersion angle (1 kHz): H=100°, V=3°  
Weight: 15 kg

[www.pssso.de](http://www.pssso.de)



**⚠ CAUTION ⚠**

Read and understand user manual before operating this product. Operation only by trained persons. Secondary attachment for overhead installation! Suspension only by Pros! Danger to life due to crashing speaker-systems. Keep away cigarettes, open fire, heaters etc. Treat the surface with fire retardant in regular intervals. Loud noise hazard. Ear protection must be worn.