



9MM

ROADINGER Flightcase 2x PAS-212

Professional flightcase for 2 x PAS-212, with castors

- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, large steel ball corners
- 4 castors, 2 of which with locking brakes
- 4 large butterfly locks (w/o locking function)
- 2 hinged, zinc-plated case handles



No. 31000450

Technical specifications:

Maximum load:	50 kg
Strength:	9 mm
Outside dimensions (WxDxH):	870 x 450 x 800 mm
Interior dimensions:	
Mounting width:	805 mm
Mounting height:	620 mm
Mounting depth:	380 mm
Outer dimensions/corners:	64 mm
Weight:	30 kg



9MM

ROADINGER Flightcase 2x PAS-215

Professional flightcase for 2 x PAS-215, with castors

- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, large steel ball corners
- 4 castors, 2 of which with locking brakes
- 4 large butterfly locks (w/o locking function)
- 2 hinged, zinc-plated case handles



No. 31000451

Technical specifications:

Maximum load:	60 kg
Strength:	9 mm
Outside dimensions (WxDxH):	960 x 510 x 920 mm
Interior dimensions:	
Mounting width:	885 mm
Mounting height:	700 mm
Mounting depth:	435 mm
Interior dimensions 2 compartments (each):	
Mounting width:	420 mm
Mounting height:	700 mm
Mounting depth:	435 mm
Outer dimensions/corners:	64 mm
Weight:	34.6 kg



7MM

ROADINGER Flightcase 2x CLA-115

Flightcase with castors for two CLA-115 Line Array Subs

- Two parts
- Bottom and cover upholstered with foam (extra strong, gray)
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, large steel ball corners
- 10 large butterfly locks
- 10 wheels
- 8 hinged, nickel-plated case handles
- 6 castors (100 mm), 2 of which have brakes



No. 11040997

Technical specifications:

Maximum load:	120 kg
Strength:	7 mm
Outside dimensions (WxDxH):	1680 x 820 x 805 mm
Interior dimensions:	
Mounting width:	1610 mm
Mounting height:	600 mm
Mounting depth:	760 mm
Outer dimensions/corners:	75 mm
Weight:	76 kg



7MM

ROADINGER Flightcase 2x CLA-212

Flightcase with castors for two CLA-212 Line Array Subs

- Two parts
- Bottom and cover upholstered with foam (extra strong, gray)
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, large steel ball corners
- 6 large butterfly locks
- 10 wheels
- 4 hinged, nickel-plated case handles
- 6 castors (100 mm), 2 of which have brakes



No. 11040996

Technical specifications:

Maximum load:	120 kg
Strength:	7 mm
Outside dimensions (WxDxH):	1200 x 830 x 730mm
Interior dimensions:	
Mounting width:	1140 mm
Mounting height:	535 mm
Mounting depth:	765 mm
Outer dimensions/corners:	75 mm
Weight:	47 kg