



K-208
K-210
K-212
K-215



K-215SE



K-315 HD

K-215DPX



PSSO K 2-way top

Pro PA speaker system

- Rugged full-range top speaker
- Qualified for suspension and touring applications
- 20-38 cm (8 - 15") mids speaker with diecast aluminum basket
- Rotatable 25 mm constant directivity horn tweeter (1", 44 mm voice coil)
- 215SE with rotatable 38 mm (1.5") constant directivity horn tweeter with 72 mm (2.8") titanium diaphragm (only 215SE)
- Housing made of 15 mm birch plywood
- Passive 2-way crossover

PSSO K-315HD 3-way top 1000W

Pro PA speaker system

- Biamp operation
- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of birch plywood
- 38 cm (15") bass speaker and 16.5 cm (6.5") midrange speaker with diecast aluminum basket
- 36 mm hybrid horn tweeter (1.4") with 72 mm voice coil (2.8")

PSSO K-215DPX 2-way top 1000W

Pro PA speaker system

- Rugged full-range top speaker (bassreflex), qualified for suspension and touring applications
- Transport wheels
- 2 x 38 cm (15") mids speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter - horn exit 50 mm (2"), voice coil 25 mm (1")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Premium passive 2-way crossover
- Parallel Neutrik Speakon connectors

No. 11041098	K-208
No. 11041100	K-210
No. 11041104	K-212
No. 11041108	K-215
No. 11041109	K-215SE
No. 11041096	K-215DPX
No. 11041112	K-315HD

Technical specifications:

Device:	K-208	K-210	K-212	K-215	K-215SE	K-215DPX	K-315 HD
Rated power:	200 W RMS	300 W RMS	300 W RMS	400 W RMS	600 W RMS	1000 W RMS	700 W RMS LF, 300 W RMS MHF
Components:	20 cm woofer (8"), 2.5 cm horn (1")	25 cm woofer (10"), 2.5 cm horn (1")	30 cm woofer (12"), 2.5 cm horn (1")	38 cm woofer (15"), 2.5 cm horn (1")	38 cm woofer (15"), 3.8 cm horn (1.5")	2 x 38 cm Woofer (15"), 2.5 cm Horn (1")	38 cm woofer (15"), 16.5 cm driver (6.5"), 3.6 cm horn tweeter (1.4")
Connections:	2 x Speakon	2 x Speakon	2 x Speakon	2 x Speakon	2 x Speakon	2 x Speakon	2 x Speakon
Sensitivity (1 W/m):	95 dB	96 dB	97 dB	98 dB	99 dB	101 dB (1 W, 1 m)	98 dB LF, 108 dB MHF
Max. SPL:	124 dB (1 m)	127 dB (1 m)	128 dB (1 m)	130 dB (1 m)	127 dB (1 m)	136 dB (1 m)	137 dB (1 m)
Impedance:	8 ohms	8 ohms	8 ohms	8 ohms	8 ohms	4 Ohm	8 ohms LF, 8 ohms MHF
Frequency range:	57 Hz - 20 kHz	55 Hz - 19 kHz	55 Hz - 19 kHz	47 Hz - 19 kHz	47 Hz - 19 kHz	44 Hz - 19 kHz	45 Hz - 20 kHz
Crossover frequency:	1.8 kHz	2 kHz	1.9 kHz	1.7 kHz	1.5 kHz	1,6 kHz	500 Hz and 2.5 kHz
Dispersion angle (HxV):	90° x 60°	90° x 60°	90° x 60°	80° x 50°	80° x 50°	70° x 50°	70° x 40°
Dimensions (HxWxD):	270 x 445 x 270 mm	340 x 540 x 320 mm	347 x 660 x 352 mm	710 x 445 x 415 mm	710 x 445 x 415 mm	1170 x 465 x 478 mm	800 x 445 x 443 mm
Weight:	12 kg	16 kg	19 kg	26 kg	32 kg	52 kg	35 kg