

PRESETS K-315HD

Section	Recommended Amplifier	Relative Gain	Polarity	Delay	High-pass	Low-pass	EQ	LIMITER
K-153HD + K-182 Subwoofer (95 Hz and 500 Hz acoustic crossover points)								
MHF 6.5" + 1.4" (8 Ω)	>400 W / 8 Ω <600 W / 8 Ω	-7 dB	+	0 ms	565 Hz 24 dB LR	OFF	-3 dB 2700 Hz 0.40 oct (Q=3) -3 dB 9200 Hz 0.30 oct (Q=3.7)	Threshold: 45 Vrms = 250 W / 8 Ω Ratio: 6:1 Attack: 15 ms Release: 10X (150 ms)
LF 15" (8 Ω)	>900 W / 8 Ω <1600 W / 8 Ω	0 dB	+	0.249 ms	95 Hz 24 dB LR	400 Hz 24 dB BW	+2 dB 200 Hz LoShelf 12dB -6 dB 200 Hz 0.33 oct (Q=3.5) -3 dB 600 Hz 0.28 oct (Q=3.9)	Threshold: 72 Vrms = 650 W / 8 Ω Ratio: 6:1 Attack: 50 ms Release: 10X (500 ms)
SUB 2 x 18" (4 Ω)	>2000 W / 4 Ω	+2 dB	+	0 ms	30 Hz 24 dB BW	95 Hz 24 dB LR	+2 dB 90 Hz 0.20 oct (Q=7)	Threshold: 98 Vrms = 2400 W / 4 Ω Ratio: 6:1 Attack: 50 ms Release: 10X (500 ms)