



PSSO K 2-way coaxial wedge

Pro PA coaxial wedge

- Rugged 2-way coaxial wedge (bassreflex), qualified for touring applications
- 25/30/38 cm (10/12/15") bass speaker with diecast aluminum basket
- 25/36 mm horn tweeter (1/2.8", 44/72 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Premium passive 2-way crossover
- Parallel Neutrik Speakon connectors
- Flange for stand installation
- Can be used as sidefill

No. 11041115K-210CM
 No. 11041117K-212CM
 No. 11041119K-215CM



Technical specifications:

Device:	K-210CM	K-212CM	K-215CM
Rated power:	300 W RMS	400 W RMS	400 W RMS
Components:	25 cm woofer (10"), 2.5 cm horn (1")	30 cm woofer (12"), 3.6 cm horn (1.4")	38 cm woofer (15"), 3.6 cm horn (1.4")
Connections:	2 x Speakon	2 x Speakon	2 x Speakon
Sensitivity (1 W/m):	96 dB	98 dB	99 dB
Max. SPL:	127 dB (1 m)	130 dB (1 m)	131 dB (1 m)
Impedance:	8 ohms	8 ohms	8 ohms
Frequency range:	68 Hz - 20 kHz	65 Hz - 19 kHz	58 Hz - 19 kHz
Crossover frequency:	1.8 kHz	1.5 kHz	1.5 kHz
Dispersion angle (HxV):	75° x 75°	70° x 70°	70° x 70°
Dimensions (HxWxD):	260 x 444 x 390 mm	297 x 504 x 437 mm	352 x 580 x 502 mm
Weight:	15 kg	19 kg	25 kg