



**PSSO PRIME Club speaker system**

Pro PA speaker system

- Pro PA speaker for clubs
- Qualified for suspension
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 2 x 20 cm ferrite bass/mids speaker (8"), 2 x 30 cm neodymium bass/mids speaker (12") with diecast aluminum basket
- 25/36 mm driver (1/1.4"), 51/72 mm voice coil (2/2.8")
- Bassreflex system
- Neutrik Speakon connectors

No. 11041168.....PRIME-208  
 No. 11041170.....PRIME-212

**Technical specifications:**

Device:	PRIME-208	PRIME-212
Rated power:	400 W RMS	1000 W RMS LF, 100 W RMS HF
Components:	2 x 20 cm woofer (8"), 2.5 cm horn tweeter (1"), 51 mm voice coil	2 x 30 cm woofer (12"), 3.6 cm horn tweeter (1.5"), 72 mm voice coil
Connections:	2 x Speakon	2 x Speakon, 4-pin
Sensitivity (1 W/m):	98 dB	101 dB
Max. SPL:	130 dB (1 m)	137 dB (1 m)
Impedance:	4 ohms	4 ohms LF, 8 ohms HF
Frequency range:	56 Hz - 19 kHz	55 Hz - 19 kHz
Crossover frequency:	1.5 kHz	1.2 kHz
Dispersion angle (HxV):	50° to 100° x 10° to -30°	50° to 100° x 10° to -30°
Dimensions (HxWxD):	400 x 530 x 420 mm	348 x 756 x 494 mm
Weight:	22 kg	34 kg



**PSSO PRIME Subwoofer**

Pro PA subwoofer

- Rugged pro PA bassreflex subwoofer for clubs
- Housing made of birch plywood
- 2 x 38/45 cm (15"/18") bass speaker with diecast aluminum basket
- Parallel Neutrik Speaker connectors

No. 11041177.....PRIME-152, 1400W  
 No. 11041178.....PRIME-182, 3000W

**Technical specifications:**

Device:	PRIME-208	PRIME-212
Rated power:	1400 W RMS	3000 W RMS
Components:	2 x 38 cm woofer (2 x 15"), 100 mm voice coil	2 x 45 cm woofer (2 x 18")
Connections:	2 x Speakon	2 x Speakon
Sensitivity (1 W/m):	99 dB	101 dB
Max. SPL:	136 dB (1 m)	142 dB (1 m)
Impedance:	4 ohms	4 ohms
Frequency range:	39 - 1600 Hz	35 - 1300 Hz
Dimensions (HxWxD):	505 x 950 x 505 mm	594 x 1094 x 695 mm
Weight:	63 kg	88 kg



**PSSO PRIME-315 Club speaker system**

Pro PA speaker system

- Rugged pro PA speaker for clubs
- Biamp operation
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 2 x 38 cm neodymium bass speaker (12") with diecast aluminum basket
- 16.5 cm neodymium midrange speaker (6.5") with diecast aluminum basket, 51 mm voice coil (2")
- 36 mm neodymium driver (1.4"), 72 mm voice coil (2.8")
- Bassreflex system
- Neutrik Speakon connectors



No. 11041172

**Technical specifications:**

Rated power:	1800 W RMS LF 300 W RMS HF
Components:	2 x 38 cm bass/mid speakers (15"), 16.5 cm horn tweeter (6.5"), 2 x 3.6 cm horn tweeter (1.4"), 72 mm voice coil
Connections:	2 x Speakon, 4-pin
Sensitivity (1 W/m):	102 dB
Max. SPL:	140 dB (1 m)
Impedance:	4 ohms LF 8 ohms HF
Frequency range:	46 Hz - 19 kHz
Crossover frequency:	650 Hz, 2.2 kHz
Dispersion angle (HxV):	80° x 50°
Dimensions (HxWxD):	815 x 838 x 584 mm
Weight:	75 kg