



EUROLITE Cable tie

No. 30006046	200 x 2,2 mm, white
No. 30006051	200 x 2,2 mm, black
No. 30006056	200 x 2,5 mm, white
No. 30006061	200 x 2,5 mm, black
No. 30006066	200 x 2,9 mm, white
No. 30006076	200 x 4,5 mm, white
No. 30006081	200 x 4,5 mm, black
No. 30006086	200 x 4,8 mm, white
No. 30006091	200 x 4,8 mm, black



HASE Gloves 3 finger
Professional gloves for roadies
• 3 fingers version

No. 78020396	M
No. 78020401	L
No. 78020403	XL



EUROLITE Floor cable channel 75mm silver
Rugged floor cable channel

- With slip-resistant surface on the cover
- Wheelchairs can easily overcome the channel
- Extreme stability
- Easy installation
- Low weight

No. 51210852	2 m
No. 51210854	4 m



EUROLITE LM-50 Lux meter
Digital light meter for a fast illumination measurement
• 3 selectable measuring ranges from 0-50,000 lux
• Auto zero adjustment

No. 10360620

Technical specifications:

Power supply:	9 V battery
Measuring ranges lux:	0-2000 lx, 2000-20000 lx (measurand x 10), 20000-50000 lx (measurand x 100)
Accuracy:	± 5 % + 2 digits within 22-28 °C
Calibration:	Standard incandescent lamp at color temperature 2856 kelvin
Sampling rate:	0.4 measurements per second
Dimensions (LxWxH):	115 x 70 x 30 mm
Weight:	0.3 kg



EUROLITE LM-200 Lux meter
Digital light meter for a fast illumination measurement
• 4 selectable measuring ranges
• Peak function

No. 10360630

Technical specifications:

Power supply:	9 V battery
Battery life:	approx. 200 hrs.
Measuring ranges lux:	0-200 lx, 200-2000 lx, 2000-20000 lx (measurand x 10), 20000-200000 lx (measurand x 100)
Accuracy:	± 3 % rdg ± 5 % fs <= 20000 lux, ± 5 % rdg ± 10 digits = 20000 lx
Calibration:	Standard incandescent lamp at color temperature 2856 kelvin
Repeatability:	± 2 %
Temperature characteristic:	± 0,1 %/°C
Sampling rate:	2 measurements per second
Measuring electrode:	Silicon photodiode with filter
Dimensions (LxWxH):	160 x 80 x 40 mm
Weight:	0.3 kg