



ROADINGER Mixer case Pro MCV-19, variable, bk

Professional flightcase for 483 mm units (19")

- Suitable for 483 mm units (19"), e.g. controllers and mixers
- Upward tiltable profile rails for top-operated units
- Aluminum profile frames (25 mm) with rounded edges
- Removable cover
- Three-leg, medium-sized steel ball corners
- 2 high-quality lockable butterfly locks
- 4 steel-enforced rubber feet

Technical specifications 8 U:

Maximum load:	15 kg
Strength:	6 mm
Outside dimensions (WxDxH):	530 x 440 x 240 mm
Inside dimensions:	
Mounting width:	490 mm, 19"
Mounting height:	110 to 200 mm
Mounting depth:	390 mm, 8 U
Outer dimensions/corners:	55 mm
Weight:	7 kg

Technical specifications 12 U:

Maximum load:	25 kg
Strength:	6 mm
Outside dimensions (WxDxH):	535 x 620 x 265 mm
Inside dimensions:	
Mounting width:	483 mm, 19"
Mounting height:	90 to 180 mm
Mounting depth:	545 mm, 12 U
Outer dimensions/corners:	55 mm
Weight:	9 kg

No. 3011157A 8 U
 No. 3011157D 12 U



9MM 19"

ROADINGER Rack Profi 1U 25cm

PRO flightcase for 483 mm units (19")

- 2 removable covers (double-door version)
- With 9 mm multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners
- 2 recessed case handles with mounting dish and backing ring
- 4 butterfly locks



No. 30109160

Technical specifications:

Length:	540 mm
Width:	420 mm
Height:	115 mm
Mounting height:	44 mm (1 HE)



9MM 19"

ROADINGER Rack Profi KM with wheels

PRO flightcase for 483 mm units (19")

- Profile rails with mounting facility for 483 mm units (19"), e.g. light PA amplifiers, power packs, additional equipment
- Stomped profile rails for cage nuts
- 2 removable covers (double-door version)
- With 9 mm multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners



wheels



No. 30109190 55 cm, 6U, with wheels
 No. 30109192 55 cm, 8U, with wheels
 No. 30109194 55 cm, 10U, with wheels
 No. 30109196 55 cm, 12U, with wheels
 No. 30109198 55 cm, 16U, with wheels



Technical specifications:

Device:	6U	8U	10U	12U	16U
Maximum load:	50 kg	50 kg	50 kg	50 kg	100 kg
Strength:	9 mm	9 mm	9 mm	9 mm	
Outside dimensions (WxDxH):	530 x 710 x 430 mm	530 x 710 x 520 mm	530 x 710 x 605 mm	530 x 710 x 695 mm	700 x 530 x 875 mm
Interior dimensions:					
Mounting width:	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	
Mounting height:	275 mm (6 U)	360 mm (8 U)	450 mm (10 U)	540 mm (12 U)	711 mm (16 U)
Mounting depth:	approx. 550 mm	approx. 550 mm	approx. 550 mm	approx. 550 mm	
Corner dimensions:	65 mm	65 mm	65 mm	65 mm	
Weight:	20 kg	21.5 kg	23.5 kg	25.5 kg	