



ROADINGER Amplifier rack PR-2

Professional flightcase for 483 mm units (19")


- Profile rails with mounting facility for 483 mm units (19")
- Front and rear rack rails
- 2 removable covers (double-door version)
- Max. depth 420 mm (plus 90 mm per cover)
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners
- 4 high-quality butterfly locks (w/o locking function)
- 2 wooden slide rails on the bottom
- 2 hinged, chromium plated case handles



No. 30109784.....	4 U
No. 30109786.....	6 U
No. 30109788.....	8 U
No. 30109790.....	10 U
No. 30109792.....	12 U
No. 30109794.....	14 U
No. 30109798.....	16 U
No. 30109800.....	18 U
No. 30109805.....	20 U
No. 3010980E.....	12 U, wheelboard
No. 3010980H.....	14 U, wheelboard
No. 3010980K.....	16 U, wheelboard
No. 3010980M.....	18 U, wheelboard
No. 3010980N.....	20 U, wheelboard

Technical specifications:

Device:	30109784	30109786	30109788	30109790	30109792	30109794	30109798	30109800	30109805
Maximum load:	25 kg	50 kg	50 kg	100 kg	100 kg	100 kg	100 kg	100 kg	100 kg
Strength:	7 mm	7 mm	9 mm	7 mm	9 mm	7 mm	6 mm	7 mm	9 mm
Outside dimensions (WxDxH):	545 x 640 x 220 mm	545 x 640 x 320 mm	680 x 560 x 405 mm	680 x 560 x 500 mm	550 x 680 x 600 mm	680 x 560 x 680 mm	550 x 680 x 770 mm	680 x 560 x 860 mm	550 x 690 x 950 mm
Interior dimensions:									
Mounting width:	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")
Mounting height:	180 mm (4 U)	270 mm (6 U)	360 mm (8 U)	450 mm (10 U)	540 mm (12 U)	635 mm (14 U)	725 mm (16 U)	815 mm (18 U)	900 mm (20 U)
Mounting depth:	420 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)	470 mm (90 mm per cover)
Corner dimensions:	64 mm	64 mm	64 mm	64 mm	64 mm	64 mm	64 mm	64 mm	64 mm
Weight:	approx. 10 kg	11.5 kg	16 kg	20 kg	22 kg	24 kg	31 kg	32 kg	34 kg



ROADINGER Amplifier rack PR-2ST

Professional flightcase for 483 mm units (19")

- Profile rails with mounting facility for 483 mm units (19")
- Front and rear rack rails
- 2 removable covers (double-door version)
- Max. depth 550 mm (plus 90 mm per cover)
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners
- 4 high-quality butterfly locks (w/o locking function)
- 2 wooden slide rails on the bottom
- 4 hinged, chromium plated case handles



No. 30109785.....	4 U
No. 30109787.....	6 U
No. 30109789.....	8 U
No. 30109791.....	10 U
No. 30109793.....	12 U
No. 30109799.....	16 U
No. 3010982A.....	12 U, wheelboard
No. 3010982C.....	14 U, wheelboard
No. 3010982E.....	16 U, wheelboard
No. 3010982G.....	18 U, wheelboard
No. 3010982J.....	20 U, wheelboard

Technical specifications:

Device:	30109785	30109787	30109789	30109791	30109793	30109799	30109801
Maximum load:	50 kg	60 kg	100 kg	100 kg	100 kg	100 kg	
Strength:	7 mm	7 mm	9 mm	9 mm	9 mm	9 mm	9 mm
Outside dimensions (WxDxH):	545 x 640 x 220 mm	790 x 550 x 310 mm	800 x 550 x 405 mm	550 x 805 x 505 mm	550 x 800 x 600 mm	550 x 800 x 685 mm	550 x 810 x 860 mm
Interior dimensions:							
Mounting width:	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")
Mounting height:	180 mm (4 U)	265 mm (6 U)	360 mm (8 U)	450 mm (10 U)	545 mm (12HE)	635 mm (14 U)	810 mm (18 U)
Mounting depth:	550 mm (90 mm per cover)	550 mm (90 mm per cover)	550 mm (90 mm per cover)	550 mm (90 mm per cover)	550 mm (90 mm pro Deckel)	550 mm (90 mm per cover)	550 mm (90 mm per cover)
Exterior corner dimensions:	approx. 64 mm	64 mm	64 mm	64 mm	56 mm	56 mm	56 mm
Weight:	10 kg	13.5 kg	20 kg	20 kg	24 kg	25 kg	33 kg



9MM

ROADINGER Amplifier rack SP-2, shock-proof

Professional flightcase for 483 mm units (19"), shock-proof

- Profile rails with mounting facility
- 2 removable covers (double-door version)
- Covers upholstered with foam (25 mm) for damping during transport
- Max. depth: behind the front panel 420 mm, max. depth in front panel 90 mm
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners
- 4 high-quality butterfly locks
- 2 hinged, chromium plated case handles

No. 30109710.....	4 U
No. 30109712.....	6 U
No. 30109714.....	8 U
No. 30109716.....	10 U

Technical specifications:

Device:	30109710	30109712	30109714	30109716
Maximum load:	50 kg	60 kg	100 kg	100 kg
Strength:	7 mm	7 mm	9 mm	9 mm
Outside dimensions (WxDxH):	545 x 640 x 220 mm	790 x 550 x 310 mm	800 x 550 x 405 mm	550 x 805 x 505 mm
Interior dimensions:				
Mounting width:	483 mm (19")	483 mm (19")	483 mm (19")	483 mm (19")
Mounting height:	180 mm (4 U)	265 mm (6 U)	360 mm (8 U)	450 mm (10 U)
Mounting depth:	550 mm (90 mm per cover)	550 mm (90 mm per cover)	550 mm (90 mm per cover)	550 mm (90 mm per cover)
Exterior corner dimensions:	approx. 64 mm	64 mm	64 mm	64 mm
Weight:	10 kg	13.5 kg	20 kg	20 kg