



ROADINGER Mixer case Road MCB-12 sloping 8U bk

Professional flightcase for 305 mm units (12")

- Suitable for 305 mm mixers (12") up to 8 U
- Upward tilted profile rails for top-operated units
- Aluminum profile frames (25 mm) with rounded edges
- Removable cover
- Three-leg, medium-sized steel ball corners
- 2 high-quality butterfly locks

No. 30111516

Technical specifications:

Maximum load:	25 kg
Strength:	6 mm
Outside dimensions (WxDxH):	440 x 380 x 225 mm
Weight:	7 kg



ROADINGER Mixer case Pro MCB-19, sloping

Professional flightcase for 483 mm units (19")

- Suitable for 483 mm mixers (19") from 6 up to 16 U
- Upward tilted profile rails for top-operated units
- Aluminum profile frames (25 mm) with rounded edges
- Removable cover
- Three-leg, medium-sized steel ball corners
- 2 high-quality lockable butterfly locks
- 4 rubber feet

No. 3011151A.....	black, 6 U
No. 30111560.....	black, 8 U
No. 30111565.....	black, 10 U
No. 30111561.....	black, 12 U
No. 30111567.....	black, 14 U
No. 30111568.....	black, 16 U

Technical specifications:

Device:	3011151A	30111560	30111565	30111561	30111567	30111568
Maximum load:	25 kg	15 kg	25 kg	25 kg	25 kg	25 kg
Strength:	7 mm	6 mm	6 mm	7 mm	7 mm	7 mm
Outside dimensions (WxDxH):		approx. 545 x 455 x 240 mm	approx. 530 x 800 x 240 mm	approx. 550 x 615 x 240 mm		approx. 530 x 800 x 240 mm
Inside dimensions:						
Mounting width:		approx. 490 mm, 19"	490 mm, 19"	approx. 490 mm, 19"	490 mm, 19"	490 mm, 19"
Mounting height:		approx. 205 mm	190 mm	approx. 190 mm	175 mm	175 mm
Mounting height front:		approx. 110 mm	ca. 110 mm	approx. 90 mm	670 mm, 14 U	
Mounting depth:		approx. 405 mm, 8 u	ca. 180 mm	approx. 545 mm, 12 u		760 mm, 16 U
Mounting height rear:		approx. 180 mm	510 mm, 10 U	approx. 180 mm		
Outside dimensions (LxDxH):	545 x 350 x 240 mm	approx. 55 mm	55 mm	approx. 55 mm	55 mm	55 mm
Weight:	6.5 kg	approx. 8.5 kg	ca. 8,7 kg	approx. 8.5 kg	10 kg	12 kg



ROADINGER Mixer case Pro MCBL-19

Professional flightcase for 483 mm units (19")

- Suitable for 483 mm units (19")
- Upward tilted profile rails for top-operated units
- Aluminum profile frames (25 mm) with rounded edges
- Removable cover
- Three-leg, medium-sized steel ball corners
- 2 high-quality lockable butterfly locks
- 4 steel-enforced rubber feet

Technical specifications 8 U:

Maximum load:	15 kg
Strength:	6 mm
Outside dimensions (WxDxH):	approx. 545 x 455 x 240 mm
Inside dimensions:	
Mounting width:	approx. 490 mm, 19"
Mounting height:	approx. 205 mm
Mounting height front:	approx. 110 mm
Mounting depth:	approx. 405 mm, 8 u
Mounting height rear:	approx. 180 mm
Outer dimensions/corners:	approx. 55 mm
Weight:	approx. 7.7 kg



Technical specifications 12 U:

Maximum load:	25 kg
Strength:	7 mm
Outside dimensions (WxDxH):	approx. 550 x 615 x 240 mm
Inside dimensions:	
Mounting width:	approx. 490 mm, 19"
Mounting height:	approx. 190 mm
Mounting height front:	approx. 90 mm
Mounting depth rear:	approx. 180 mm
Mounting depth:	approx. 545 mm, 12 u
Outer dimensions/corners:	approx. 55 mm
Weight:	approx. 9 kg

No. 3011155X.....	8 U
No. 3011155Z.....	12 U