



## NC3FX1-TOP

3-poliger Kabelstecker, TRUE OUTDOOR PROTECTION (TOP), vergoldete Kontakte.

Geschützt nach IP65 für Aussenanwendungen in gestecktem Zustand mit entsprechendem Gegenstecker/Buchse der XLT-TOP Serie.

### Features & Benefits

- Abgedichteter XLR-Stecker für den Einsatz in rauen Umgebungen mit höchsten Anforderungen.
- Schlagfestes UV-beständiges Material
- Schutzklasse IP65
- Erfüllt TOP Anforderungen in Anlehnung an UL50E

## Technische Informationen

Produkte	
Title	NC3FX1-TOP
Connection Type	XLR
Gender	female

Elektrisch	
Capacitance between contacts	$\leq 4$ pF
Contact resistance	$\leq 3$ m $\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10$ G $\Omega$ (initial)
Rated current per contact	16 A
Rated voltage	$< 50$ V

Mechanische Daten	
Cable O.D.	5.0 - 8.0 mm
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 5000$ mating cycles
Wiresize (mm <sup>2</sup> )	max. 1.5 mm <sup>2</sup>
Wiresize (AWG)	max. 16 AWG
Wiring	Solder contacts
Locking device	Latch lock

Material	
Bushing	UV-resistant rubber
Contact plating	Gold (Au) over Nickel (Ni)
Contacts	Bronze (CuSn8)
Insert	Polyamide (PA66)
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Nickel
Strain relief	Polyacetal
Sealing jacket	UV-resistant rubber

Umwelt	
Flammability acc. to UL94	V0 (insert)
Standard compliance	IEC 61076-2-103
Protection class acc. to OEC 60529	IP 65 (mated)
Solderability standard	IEC 60068-2-20
Temperature range	-30 °C to +80 °C
Polltion degree acc. to IEC 60664-1	II