

**Description:** C14 Dual Lock to C13 IEC Lock+ Small Connector 3G (1.00mm<sup>2</sup> H05VV-F / 17AWG SJT) Universal Cable Black - 1 Metre



## General Information

<b>Complete Powerlead Rating</b>	EU, AS/NZS: 10A 250V~ US, CSA, JPN: 15A 250V~	
	<b>C14 Dual Lock Connector</b>	<b>C13 IEC Lock+ Small Connector</b>
<b>Component Rating</b>	EU, AS/NZS: 10A 250V~ US, CSA, JPN: 15A 250V~	EU, AS/NZS: 10A 250V~ US, CSA, JPN: 15A 250V~
<b>Colour</b>	Black/Red	Black/Red
<b>Materials</b>	Over Moulding Cover: PVC Pins: Brass Strip Housing: PBT	Terminal Housing, Handle: Nylon (PA66) Over Mould: PVC Lock Lever & Red button: Polycarbonate Terminal Caddy: Nylon, Terminal: Brass Spring: 0.35mm Spring Steel, Locking Blade: Steel

## Cable Specification

<b>Cable Colour</b>	Black	<b>Insulation Material</b>	PVC (Colour Coded)
<b>Number of Conductors</b>	3	<b>Insulation Wall Thickness (mm)</b>	0.76mm
<b>Conductor Cross Sectional Area</b>	1.04mm <sup>2</sup>	<b>Insulation Elongation</b>	100%
<b>Number of Strands</b>	51	<b>Insulation Tensile Strength</b>	1500PSI
<b>Conductor Material</b>	Bare Copper (99.97%)	<b>Nominal Resistance</b>	19.5MΩ/Km Ohm/Km
<b>Jacket Material</b>	PVC	<b>Overall Cable Diameter</b>	8mm
<b>Jacket Wall Thickness</b>	0.8mm	<b>Bend Radius</b>	40°
<b>Jacket Elongation</b>	100%	<b>Rated Temperature</b>	-20 to +105°C
<b>Jacket Tensile Strength</b>	1500PSI		

## Additional Information

<b>Cable Hanking</b>	None
<b>Lock Retention</b>	> 100N
<b>Features</b>	Quick connect from single terminal Class I protection Cable cores: Brown, Blue, Yellow/Green

<b>Standards</b>	IEC /BS EN 60320-1:2015 IEC /BS EN 60320-3:2014 BS EN 50525-2-11 IEC /BS EN 60320-1:2015 IEC /BS EN 60320-3:2014 BS EN 50525-2-11
------------------	--

