



**SOMMER CABLE HDMI cable Ergonomic**

Sommer Cable HIE-HDHD multimedia cable

- HDMI High Speed with Ethernet & ARC connection cable, digital
- HDMI to HDMI cable
- Four different lengths: 0,75 m, 1,5 m, 3 m, 5 m

**Technical specifications:**

Material,jacket Ø:	S-PVC 9.0 mm
No. of inner conductors:	AWG26/AWG28
CU quality grade:	OxygenFreeCopper Class 4 (99,99 %)
Conductor insulation:	Skin PE, gas injected
Shielding:	TP: 2 x foil / Overall: 1 x copper braiding, tinned + AL/PT-foil
Shielding factor:	100 %
Temperature range:	-25 °C...+75 °C
Capac. cond./shield. @ 1 m:	52 pF
Surge impedance:	100 Ohm ± 5 %
Signal transmission or shielding coefficient:	Full HD: 2160p/24Hz, HDCP
Band width:	10.2 Gbit/s = 340 MHz
Connector material:	Polyamide
Contacts:	Brass 5 µm Au hard alloy

No. 3022803A.....	0.75 m
No. 3022803C.....	1,5 m
No. 3022803E.....	3 m
No. 3022803G.....	5 m



**SOMMER CABLE SUB-D cable bk**

SVGA monitor cable

- Matching for the formats: VGA 640x480, SVGA 800x600, XGA 1024x768, SXGA 1280x1024, UXGA 1600x1200, HDTV 1920x1080, QXGA 2048x1536
- Connection A: HD-SubD 15-pol male
- Connection B: HD-SubD 15-pol male

No. 3030736A.....	1.8 m
No. 3030736B.....	3 m
No. 3030736C.....	5 m
No. 3030736D.....	10 m
No. 3030736F.....	20 m



**SOMMER CABLE Koax cable Focusline L**

Coaxial cable

- Cable: SC-FOCUSLINE, 1 x 0.60 mm wire
- Connection A: Hicon BNC plug
- Connection B: Hicon BNC plug

No. 3030736K.....	1 m
No. 3030736L.....	3 m
No. 3030736M.....	5 m