



**EUROLITE Quick link**

Official quick link

- Complies with DIN 56927:2009-03
- Temperature range: -40° C to +100° C

No. 50301636.....	.....type B-550
No. 50301638.....	.....type B-350
No. 50301642.....	.....type A-50
No. 50301643.....	.....type A-50 black
No. 50301644.....	.....type A-90
No. 50301648.....	.....type A-200
No. 5030164B.....	.....type A-350
No. 50301655.....	.....type B-90
No. 50301659.....	.....type B-90 black
No. 50301657.....	.....type B-140
No. 5030165A.....	.....type B-140 black
No. 50301640.....	.....type B-200
No. 5030165B.....	.....type B-200 black

**Technical specifications:**

Identification:	DIN 56926 B-550	DIN 56926 B-350	DIN 56926 A-50	DIN 56926 A-50	DIN 56926 A-90	DIN 56926 A-200	DIN 56926 A-350	DIN 56926 B-90	DIN 56926 B-140	DIN 56926 B-200
Max. load BGV C1 (10-fold):	550 kg	350 kg	50 kg	50 kg	90 kg	200 kg	350 kg	90 kg	140 kg	200 kg
Identification:	DIN 56926 B-550	DIN 56926 B-350	DIN 56926 A-50	DIN 56926 A-50	DIN 56926 A-90	DIN 56926 A-200	DIN 56926 A-350	DIN 56926 B-90	DIN 56926 B-140	DIN 56926 B-200
Diameter:	10 mm	8 mm	3.5 mm	3.5 mm	4 mm	6 mm	8 mm	4 mm	5 mm	6 mm
Form:	B - large	B - large	A - small	A - small	A - small	A - small	A - small	B - large	B - large	B - large
Spanner opening:	20.5 mm	17.5 mm	5 mm	5 mm	5.5 mm	7.5 mm	11 mm	11.5 mm	13 mm	14.5 mm
Dimensions:	110 x 44 mm	100 x 38 mm	35 x 19 mm	35 x 19 mm	41 x 22 mm	58 x 27 mm				73 x 30 mm
Weight:	135 g	92 g	9 g	9 g	12 g	30 g				40 g



**EUROLITE Girder clamp black**

- Large flange range
- High carrying capacity
- Flexible use due to wide adjustment range

No. 5801108W.....	..... 1000 kg
No. 58011090.....	..... 3000 kg

**Technical specifications:**

Max. load WLL (4-fold):	1000 kg	3000 kg
Max. load BGV C1 (8-fold):	500 kg	1500 kg
Max. load BGV C1 (10-fold):	400 kg	1200 kg
Max. load BGV C1 (12-fold):	333 kg	1000 kg
Flange range:	75-230 mm	80-320 mm
Dimensions:	310 x 85 x 230 mm	370 x 120 x 330 mm
Weight:	4 kg	10 kg

**EUROLITE Lifting rope w. shackle -400kg**

Lifting rope, safety bond, safety

- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- 16 mm shackle included in the delivery



**Technical specifications:**

Max. load WLL (5-fold):	1050 kg
Max. load BGV C1 (12-fold):	450 kg
Max. load (safety):	100 kg
Temperature range:	-40° C to +100° C
Rope diameter:	10.00 mm
Rope type:	Round strand rope
Rope construction:	6 x 19 FC
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strength:	1770 N/mm <sup>2</sup>
Strength classification:	1770
Wire surface:	Zinc-plated
Mass:	0.359 kg/m

No. 58010490.....	.....1000x10 mm
No. 58010491.....	.....1500x10 mm
No. 58010492.....	.....2000x10 mm