- Universal Moving-Head
 Colour-wheel with 7 different, dichroic colour-filtres, UV-filter plus white
 Gobo-wheel with 7 static metal gobos plus open
 Gobo-wheel with 7 rotating gobos plus open

- With gobo-shake function
 Macro-function for rotating gobos/rotating prism combinations
 Motorized Multistep-Zoom (18°, 22°, 26°)
- Motorized focus
- Strobe-effect with 1-13 flashes per second
- Rotating 3-facet prism
- Stepless frost-filter for fading the projections in or out
- Dimmer • Shutter
- Shutter
 Exact positioning via 16 bit Pan/Tilt movement resolution
 Control-Board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off
 PAN-angle switchable between 630° and 540° (depending upon the software version)
 DMX-controlled operation or stand alone operation with Master/Slave-function

- 48 preprogrammed scenes in Program Run can be charged individually
 Number of scenes in Program Run can be charged individually
 The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
 8 built-in programs can be called up via DMX-controller
- · Sound-controlled via built-in microphone
- For MSD/HSD 250 or MSD 250/2 lamp
- DMX-control via every standard DMX-controller

