

**Multi-function Washlight**

- DMX-controlled operation or stand alone operation with Master/Slave-function
- 48 preprogrammed scenes in Program Run for stand alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 8 built-in programs can be called up via DMX-controller
- Sound-controlled via built-in microphone
- CMY colour mixture for indefinite colour variations
- Colour-wheel with additional 4 discrete dichroic filters plus white, 3200 K and 5600 K correction-filters, UV-filter
- Switchable colour change (mode 1: only full colours, mode 2: colour-change at every position)
- Rainbow-effect with adjustable speed in both directions
- Macro-function for combinations between CMY-colour mixture and colour-wheel
- Frost-filter for softer beam
- Beam-shape effect: wide and flat beam can steplessly be rotated by 180°
- Strobe-effect of 1-10 flash per sec.
- Control-Board with 4-digit display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt-Reverse, Program, Reset, lamp on/off, operating hours
- Remotely switching of the lamp
- Built-in demo sequence
- Preprogrammed variable/random strobe and dimmer pulse effects
- Black-out while Head moving or colour changing
- Remotely controllable speed of PAN /TILT movement for easy programming (vector mode)
- Remote reset function
- Motorized zoom
- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution
- For MSR 700 G-22 lamp
- DMX-control via every standard DMX-controller
- Suitable FUTURELIGHT controllers: CP-528 controller

**Technical specifications:**

Power supply:	230 V AC, 50 Hz ~
Power consumption:	1300 W
DMX-control-channels:	17
DMX-512-connection:	3-pin XLR
Flash-rate:	10 Hz
Colour-system:	CMY colour-mixture
Colour-wheel:	4 dichroic filters plus white, 3200 K and 5600 K correction-filters, UV-filter
Maximum PAN-movement 540°:	in 3.5 s
Maximum TILT-movement 265°:	in 2.5 s
Length of base (including handles):	530 mm
Width of yoke:	390 mm
Height (head horizontal):	570 mm
Weight (net):	37 kg

**Accessory:**

OMNILUX OSD 72V/700W G-22 2000h	No. 89104005
GE CSR 700/2 72V/700W G-22 1000h	No. 89105000
OSRAM HSR 700 72V/700W G-22 1000h	No. 89105010
PHILIPS MSR700 72V/700W G-22	No. 89105015
PHILIPS MSR700/2 72V/700W G-22 7200K	No. 89105016
FUTURELIGHT CP-240 controller	No. 51834265
FUTURELIGHT CP-528 controller 16bit	No. 51834315
Wizard-512 USB DMX-Software + Interface	No. 51860102
Wizard-1024 USB DMX-Software + Interface	No. 51860110
Flightcase for 2x PHS/PHW-700+reel-board	No. 51836865
FUTURELIGHT DES-3 DMX-terminator 3-pin	No. 51834001