

**EUROLITE LED IP T1000 RGB 10mm**

No. 51914115 ..... 20°  
 No. 51914117 ..... 40°

- + Ideal LED luminary for outdoor use
- + 240 high-power 10 mm LEDs
- + Locking possibility at the mounting bracket

DMX IP outdoor use



- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote (necessary for use)
- DMX control via regular DMX controller (occupies 5 channels)
- Ideal LED luminary for outdoor use
- Fixed installation is recommended
- Locking possibility at the mounting bracket
- Perfect in public places and in front of buildings
- The weather-resistant housing also allows operation during bad weather
- Extremely compact housing in an appealing design
- Ready for connection with power cord and safety power plug
- For the usage a DMX cable adapter is necessary

**Technical specifications:**

Power supply:	230 VAC, 50 Hz ~
Power consumption:	40 W
Number of DMX control channels:	5
Protection grade:	IP 65
LED type:	10 mm
Number of LEDs:	240
Dimensions (LxWxH):	1000 x 80 x 170 mm
Weight:	5 kg

**Accessories:**

EUROLITE TPC-10 Coupler, black	No. 59006858
EUROLITE IR remote for LED effects	No. 51914130
Button cell battery CR2025 3V	No. 14020613
DMX-adapter IN LED Par/Flood IP65, 1m	No. 51914145
DMX-adapter OUT LED Par/Flood IP65 1m	No. 51914146
Cable MC-30, 3m, black, XLR m/f, balanced	No. 3022047N
DMX-cable for LED Par/Flood IP65, 2m	No. 51914140
DMX-cable for LED Par/Flood IP65, 5m	No. 51914141

**EUROLITE LED IP T1000 RGB 24x1W 20°**

No. 51914114

- + Static colors, automatic color change, internal programs, strobe effect, Master/Slave
- + Ideal LED luminary for outdoor use
- + Fixed installation is recommended

DMX IP outdoor use HIGH POWER LED



- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote (necessary for use)
- DMX control via regular DMX controller (occupies 5 channels)
- Ideal LED luminary for outdoor use
- Fixed installation is recommended
- Locking possibility at the mounting bracket
- Perfect in public places and in front of buildings
- The weather-resistant housing also allows operation during bad weather
- Extremely compact housing in an appealing design
- Ready for connection with power cord and safety power plug
- A DMX cable adapter is recommended for use via DMX
- Illuminants: 24 1W LEDs

**Technical specifications:**

Power supply:	230 VAC, 50 Hz ~
Power consumption:	50 W
Number of DMX channels:	5
Protection grade:	IP 65
LED type:	1 W
Number of LEDs:	24
Beam angle:	20°
Dimensions (LxWxH):	1000 x 80 x 100 mm
Weight:	5 kg

**Accessories:**

EUROLITE TPC-10 Coupler, black	No. 59006858
EUROLITE IR remote for LED effects	No. 51914130
Button cell battery CR2025 3V	No. 14020613
DMX-adapter IN LED Par/Flood IP65, 1m	No. 51914145
DMX-adapter OUT LED Par/Flood IP65 1m	No. 51914146
Cable MC-30, 3m, black, XLR m/f, balanced	No. 3022047N
DMX-cable for LED Par/Flood IP65, 2m	No. 51914140
DMX-cable for LED Par/Flood IP65, 5m	No. 51914141

**EUROLITE LED IP T1000 TCL 18x3W 15°**

No. 51914119

- + Outdoor color changer
- + Highpower tricolor LEDs (18 x 3 W LED)
- + Static colors, automatic color change, 9 built-in programs and strobe effect with variable speed, Master/Slave
- + Ideal LED luminary for outdoor use

NEW TCL DMX IP outdoor use HIGH POWER LED



- Functions: static colors; automatic color change, 9 built-in programs and strobe effect with variable speed; Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote (necessary for use)
- 3, 4, 5, 6 channel DMX mode selectable
- DMX control via regular DMX controller
- Ideal LED luminary for outdoor use
- Locking possibility at the mounting bracket
- Perfect for public places and buildings
- 18 x 3 W LEDs
- Ready for connection via power cord with safety power plug

**Technical specifications:**

Power supply:	230 VAC, 50 Hz ~
Power consumption:	100 W
Number of DMX channels:	3/4/5/6
DMX connection:	3-pin screwable connector plug
Protection grade:	IP 65
LED type:	3 W
Number of LEDs:	18
Beam angle:	15°
Dimensions (LxWxH):	1000 x 80 x 100
Weight:	5 kg