

The new outdoor staff

powerful as never: with the new IP PAD series, Eurolite presents the most powerful outdoor LED spots. Six models with 4 different LED types are available. The PADs can replace halogen models with up to 1.5 kW and discharge models with up to 750 W.

Three PADs have powerful 8-Watt-LEDs. The QCL LEDs feature RGBW and only differ in the number of LEDs (4, 9 and 24). One PAD is equipped with 36 x 3 Watt tricolor LEDs (RGB).

Another one, a 60 x 3 Watt spot, features coldwhite and warm-white LEDs. With these LEDs, the color temperature can be steplessly adjusted between 3000 K and 7000 K.

Last but not least, the COB version with a powerful 150 W COB RGB LED. The IP PADs can be controlled by DMX, Stand-alone functions and remote control.

All settings like DMX-address, colours, programs can be adjusted at the spot's rear panel via LC display or remote-control.

The functions of the DMX-channels and of the remote control depend on the individual device.

Silent operation due to cooling elements, no ventilation fans.



DMX QCL RGBW IP65

EUROLITE LED IP PAD 4x8W QCL

Ultra-flexible architectural spot (IP65) with QCL LEDs and IR remote control

- Equipped with 4 x 8 W QCL LEDs in RGBW
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Cooling via housing



No. 51914156

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W
Protection grade:	IP 65
DMX control channels:	4/6/7
DMX512 connection:	3-pin screw connector
Number of LEDs:	4
LED type:	8 W QCL
Beam angle:	25°
Dimensions (LxWxH):	220 x 160 x 210 mm
Weight:	3 kg

DMX QCL RGBW IP65

EUROLITE LED IP PAD 9x8W QCL

Compact architectural spot (IP65) with QCL LEDs and IR remote control

- Equipped with 9 x 8 W QCL LED in RGBW
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Cooling via housing



No. 51914158

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
Protection grade:	IP 65
DMX control channels:	4/6/7
DMX512 connection:	3-pin screw connector
Number of LEDs:	9
LED type:	8 W QCL
Beam angle:	15°
Dimensions (LxWxH):	120 x 205 x 223 mm
Weight:	4.25 kg