



DMX COB RGB

EUROLITE LED CBB-3 COB RGB 3x15W Bar

Practical professional light bar (RGB)

- Equipped with 3 x 15 W COB LED
- 3, 5, 9, 10 or 14 DMX channel mode selectable for numerous applications
- Each LED can be controlled individually

No. 51930277

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Number of DMX channels:	3/5/9/10/14
DMX512 connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	Array Cluster 15 W, RGB
Number of LEDs:	3
Max. beam angle:	71°
Dimensions (LxWxH):	204.2 x 344 x 144.5 mm
Weight:	3 kg



DMX COB RDM NSP RGB

EUROLITE LED PMB-4 COB RGB 30W Bar NSP

LED color changing bar with narrow beam angle

- 3, 5, 12 15 or 16 DMX channels selectable for numerous applications
- Equipped with 4 x 30 W COB LED in the colors red, green and blue
- Each LED can be controlled individually
- Supports RDM (Remote Device Management)



No. 51930283

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz ~
Power consumption:	115 W
DMX control channels:	3/5/12/15/16
DMX512 connection:	5-pin and 3-pin XLR
Flash-rate:	18 Hz
Sound-control:	via built-in microphone
Number of LEDs:	4
LED type:	Array Cluster 30 W, RGB
Beam angle:	approx. 15°
Dimensions (LxWxH):	150 x 440 x 165 mm
Weight:	5kg



DMX COB RGB

EUROLITE LED PMB-4 COB RGB 30W Bar

LED color changing bar with 30 W COB LEDs, wide beam angle

- LED color changing bar with 30 W COB LEDs (Chip On Board)
- 4 COB LEDs in the colors red, green and blue
- 3, 5, 12 or 15 DMX channels selectable for numerous applications
- Each LED can be controlled individually



No. 51930284

Technical specifications:

Power supply:	230 V AC, 50 Hz ~
Power consumption:	130 W/210 VA
DMX control channels:	3/5/12/15
DMX512 connection:	3-pin XLR/5-pin XLR
Flash-rate:	18 Hz
Sound-control:	via built-in microphone
Number of LEDs:	4
LED type:	Cluster 30 W, RGB
Beam angle:	approx. 60°
Dimensions (LxWxH):	150 x 440 x 165 mm
Weight:	4.6kg