
 **SAVEKING Safety bond**
Impulse absorbing safety bond



- Safety bond with integrated drop damping
- BG certified
- Suitable for securing loads above persons
- With two thimbles
- 5 mm quick link (form B 140) included

No. 58010250.....	3x600 mm, silver
No. 58010252.....	3x600 mm, black
No. 58010254.....	3x1000 mm, silver
No. 58010256.....	3x1000 mm, black
No. 58010258.....	4x600 mm, silver
No. 58010260.....	4x600 mm, black
No. 58010262.....	4x1000 mm, silver
No. 58010264.....	4x1000 mm, black
No. 58010266.....	5x600 mm, silver
No. 58010268.....	5x600 mm, schwarz
No. 58010270.....	5x1000 mm, silver
No. 58010272.....	5x1000 mm, schwarz

EUROLITE Safety bond
Approved safety rope



- Suitable for securing loads above persons
- Round strand rope 6 x 19M with fibre core
- With two thimbles
- 3.5 mm quick link (form A) included

No. 58010310.....	3x600 mm, silver, A form
No. 58010342.....	3x600 mm, black, A form
No. 58010320.....	4x1000 mm, silver, A form
No. 58010344.....	4x1000 mm, black, A form
No. 58010345.....	4x1000 mm, black, B form
No. 58010331.....	6x1000 mm, silver, B form
No. 58010347.....	6x1000 mm, black, B form



No. 58010360.....	3x600 mm, silver, AG-5
No. 58010364.....	4x1000 mm, silver, AG-15
No. 58010369.....	6x1000 mm, silver, AG-35

Technical specifications:

Identification:	3x600mm	3x1000mm	4x600mm	4x1000mm	5x600mm	5x1000mm	3x600mm, A-Form	4x1000mm, A-Form	6x1000mm, A-Form	4x1000mm, B-Form	3x600mm, AG-5	4x1000mm, AG-10	6x1000mm, AG-35B
Max. load:	20 kg	40 kg	40 kg	40 kg	60 kg	60 kg	5 kg	15 kg	35 kg	15 kg	5 kg	15 kg	35 kg
Temperature range:							-40° C bis +100° C	-40° C bis +100° C	-40° C bis +100° C	-40° C bis +100° C	-40° C bis +100° C	-40° C bis +100° C	-40° C bis +100° C
Rope length:	1 m	0.6 m	0.6 m	1 m	0.6 m	1 m	0.60 m	1.00 m	1.00 m	1.00 m	0.60 m	1.00 m	1.00 m
Rope diameter:	3 mm	4 mm	4 mm	4 mm	5 mm	5 mm	3.00 mm	4.00 mm	6.00 mm	4.00 mm	3.00 mm	4.00 mm	6.00 mm
Rope type:							Round strand rope	Round strand rope	Round strand rope	Round strand rope	Round strand rope	Round strand rope	Round strand rope
Rope construction:							6 x 19 FC	6 x 19 FC	6 x 19 FC	6 x 19 FC	6 x 19 FC	6 x 19 FC	6 x 19 FC
Standard:							DIN EN 12385-4:2008-06, DIN 56927:2009-03	DIN EN 12385-4:2008-06, DIN 56927:2009-03	DIN EN 12385-4:2008-06, DIN 56927:2009-03	DIN EN 12385-4:2008-06, DIN 56927:2009-03	DIN EN 12385-4:2008-06, DIN 56927:2009-03	DIN EN 12385-4:2008-06, DIN 56927:2009-03	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strength:							1770 N/mm ²	1770 N/mm ²	1770 N/mm ²	1770 N/mm ²	1770 N/mm ²	1770 N/mm ²	1770 N/mm ²
Strength classification:							1770	1770	1770	1770	1770	1770	1770
Wire surface:							Zinc-plated	Zinc-plated	Zinc-plated	Zinc-plated	Zinc-plated	Zinc-plated	Zinc-plated
Mass:							0.0311 kg/m	0.0554 kg/m	0.125 kg/m	0.0554 kg/m	0.0311 kg/m	0.0554 kg/m	0.125 kg/m

EUROLITE Steel rope
Simple steel rope



- Suitable for installing light loads
- With two loops

No. 58010380.....	3x400 mm, silver
No. 58010382.....	3x400 mm, black
No. 5801048F.....	3x600 mm, silver
No. 5801049A.....	3x600 mm, black
No. 58010384.....	3x900 mm, silver
No. 58010388.....	3x900 mm, black
No. 58010392.....	4x400 mm, silver
No. 58010394.....	4x400 mm, black
No. 58010396.....	4x900 mm, silver
No. 58010398.....	4x900 mm, black
No. 5801048G.....	4x1000 mm, silver
No. 5801039A.....	4x1400 mm, silver
No. 5801039C.....	4x1400 mm, black
No. 5801039E.....	6x400 mm, silver
No. 5801039F.....	6x400 mm, black
No. 5801048L.....	6x1000 mm, silver
No. 5801049C.....	4x1000 mm, black
No. 5801049E.....	6x1000 mm, black
No. 60003861.....	1,5x345 mm Rigport, silver



No. 58010405.....	3x400 mm with connector, silver
No. 58010408.....	3x400 mm with connector, black
No. 58010410.....	3x900 mm with connector, silver
No. 58010412.....	3x900 mm with connector, black
No. 58010430.....	4x400 mm with connector, silver
No. 58010432.....	4x400 mm with connector, black
No. 58010434.....	4x900 mm with connector, silver
No. 58010436.....	4x900 mm with connector, black
No. 58010438.....	4x1400 mm with connector, silver
No. 58010440.....	4x1400 mm with connector, black
No. 58010442.....	6x400 mm with connector, silver

Technical specifications:

Identification:	3x400mm	3x600mm	3x900mm	4x400mm	4x900mm	4x1000mm	4x1400mm	6x400mm	6x1000mm	1,5x345mm	3x400mm	3x900mm	4x400mm	4x900mm	4x1400mm	6x400mm
Max. load WLL (5-fold):	90 kg	100 kg	90 kg	160 kg	160 kg	175 kg	160 kg	360 kg	400 kg		90 kg	90 kg	160 kg	160 kg	160 kg	360 kg
Rope length:	0.4 m	0.6 m	0.9 m	0.4 m	0.9 m	1 m	1.4 m	0.4 m	1 m	345 mm	0.4 m	0.9 m	0.4 m	0.9 m	1.4 m	0.4 m
Rope diameter:	3 mm	3.00 mm	3 mm	4 mm	4 mm	4.00 mm	4 mm	6 mm	6.00 mm	1,5 mm	3 mm	3 mm	4 mm	4 mm	4 mm	6 mm
Weight		0.359 kg/m				0.0554 kg/m			0.125 kg/m		0.03 kg	0.04 kg	0.06 kg	0.09 kg	0.11 kg	0.15 kg