



**EUROLITE TPC Half coupler**

- For 50 mm tube
- |                   |                  |
|-------------------|------------------|
| No. 59006856..... | TPC-10, silver   |
| No. 59006858..... | TPC-10, black    |
| No. 5900685E..... | TPC-15, silver   |
| No. 5900685F..... | TPC-15, black    |
| No. 59006859..... | TPC-20, silver   |
| No. 59006860..... | TPC-30, silver   |
| No. 59006862..... | TPC-30, black    |
| No. 59006865..... | TPC-31, silver   |
| No. 59006867..... | TPC-31, black    |
| No. 59006868..... | TPC-32, silver   |
| No. 59006870..... | TPC-35, silver   |
| No. 59006872..... | TPC-35, black    |
| No. 5900687A..... | TPC-36, silver   |
| No. 59006800..... | TPC-50, silver   |
| No. 59006802..... | TPC-50, black    |
| No. 59006848..... | TPC-51, silver   |
| No. 59006849..... | TPC-51, black    |
| No. 59006810..... | TPC-52, silver   |
| No. 59006845..... | TPC-55, silver   |
| No. 59006846..... | TPC-55, black    |
| No. 59006850..... | TPC-56, silver   |
| No. 59006851..... | TPC-56Q*, silver |

\*truss systems QLE T

**Technical specifications:**

Device:	TPC-10	TPC-15	TPC-20	TPC-30	TPC-31	TPC-32	TPC-35	TPC-36	TPC-50	TPC-51	TPC-52	TPC-55	TPC-56/TPC-56Q
Für Rohrdurchmesser:	50 mm	50 mm	20 mm	50 mm	50 mm	50 mm	50 mm	50 mm	50 mm	50 mm	50 mm	50 mm	50 mm
Max. load WLL (4-fold):	150 kg	150 kg	10 kg	500 kg	500 kg	200 kg	500 kg	200 kg	800 kg	800 kg	1000 kg	800 kg	500 kg
Max. load BGV C1 (8-fold):	75 kg	75 kg	5 kg	250 kg	250 kg	100 kg	250 kg	100 kg	400 kg	400 kg	500 kg	400 kg	250 kg
Max. load BGV C1 (10-fold):	60 kg	60 kg	4 kg	200 kg	200 kg	80 kg	200 kg	80 kg	320 kg	320 kg	400 kg	320 kg	200 kg
Max. load BGV C1 (12-fold):	50 kg	50 kg	3,3 kg	150 kg	150 kg	66 kg	150 kg	66,5 kg	250 kg	250 kg	330 kg	250 kg	150 kg
Dimensions (LxWxH):	100x90x30mm	150x80x35mm	55x40x20mm	145x115x35mm	170x120x40mm	115x120x30mm	250x115x35mm	120x30x130mm	150x115x55mm	165x115x55mm	200x130x60mm	250x120x50mm	120x50x130mm
Weight:	0,3 kg	0,3 kg	0,03 kg	0,5 kg	0,6 kg	0,4 kg	0,9 kg	0,5 kg	0,7 kg	0,8 kg	0,9 kg	1,3 kg	0,7 kg



**EUROLITE DEC coupler for 35mm**

Decolock coupler

- For 35 mm tube (e.g. for ALUTRUSS DECOLOCK)
- Width 30 mm
- Mounting screw M-10 x 20 mm with self-securing nut

- |                   |                 |
|-------------------|-----------------|
| No. 59006905..... | DEC-30, silver  |
| No. 59006908..... | DEC-30, black   |
| No. 59006915..... | DEC-30D, silver |
| No. 59006917..... | DEC-30D, black  |
| No. 59006920..... | DEC-30E, silver |
| No. 59006922..... | DEC-30E, black  |
| No. 59006960..... | Dual Ø38/50mm   |

**Technical specifications:**

Device:	DEC-30	DEC-30D	DEC-30E	Dual Ø38/50mm
Für Rohrdurchmesser:	35 mm	35 mm	35 mm	38 mm or 50 mm
Max. load WLL (4-fold):	100 kg	250 kg	250 kg	
Max. load BGV C1 (8-fold):	50 kg	125 kg	125 kg	
Max. load BGV C1 (10-fold):	40 kg	100 kg	100 kg	
Max. load BGV C1 (12-fold):	35 kg	80 kg	80 kg	
Dimensions (LxWxH):	65 x 65 x 30 mm	130 x 65 x 30 mm	110 x 65 x 30 mm	108 x 90 x 48 mm
Weight:	0.1 kg	0.2 kg	0.2 kg	0,21 kg