



EUROLITE STC-400 Lighting stand, 4m

High-quality winch-stand

- Made of steel
- 1-gear winch for easy lifting of the loads
- Automatic braking system

No. 59007006

Technical specifications:

Type:	Winch-driven stand
Construction:	DIN 15560-27, DIN EN ISO 12100-2
Certified by:	CE
Sections:	3
Max. load:	80 kg
Min. load:	25 kg
Max. height:	4.10 m
Min. height:	1.80 m
Adapter:	D = 30 mm
Base area:	D = 1.46 m
Transport dimensions:	1.80 x 0.21 x 0.19 m
Weight:	21 kg



EUROLITE STT-400/85 Winch stand TÜV/GS

High-quality winch-driven stand

- Value for money
- High quality
- High stability
- TÜV/GS certified



No. 59007040

Technical specifications:

Type:	Winch-driven stand
Construction:	DIN 15560-27, DIN EN ISO 12100-2
Certified by:	CE, TÜV/GS
Sections:	3 (60/40/34 mm)
Max. load:	85 kg
Min. load:	25 kg
Max. height:	4.00 m
Min. height:	1.75 m
Material:	2 mm steel
Steel rope:	4 mm
Adapter:	D = 35 mm
Base area:	D = 1.60 m
Transport dimensions:	1.75 x 0.30 x 0.27 m
Weight:	25 kg



EUROLITE STV-150A Follow spot stand

High-quality winch stand

- Made of steel
- 1-gear winch for easy lifting of the loads
- Automatic braking system

No. 59007121

Technical specifications:

Type:	Winch-driven stand alu
Construction:	DIN 15560-27, DIN EN ISO 12100-2
Certified by:	CE
Sections:	2
Max. load:	35 kg
Min. load:	15 kg
Max. height:	1.55 m
Min. height:	1.00 m
Adapter:	D = 30 mm
Base area:	D = 0.85 m
Transport dimensions:	1.20 x 0.27 x 0.19 m
Weight:	9 kg



EUROLITE STW-370A Winch-driven stand 370cm

High-quality winch-stand

- Aluminum version
- Ideal for mobile, professional lighting-systems or PA-systems

Technical specifications:

Type:	Winch-driven stand
Construction:	DIN 15560-27, DIN EN ISO 12100-2
Certified by:	CE
Sections:	3
Max. load:	35 kg
Min. load:	25 kg
Max. height:	3.70 m
Min. height:	1.70 m
Adapter:	D = 30 mm
Base area:	D = 1.11 m
Transport dimensions:	1.95 x 0.27 x 0.19 m

No. 60000820.....ALU, 13 kg
 No. 60000830Steel, 20 kg